

## **Profile**

## A 16-S SUPERLIGHT Professional Shallow Water **Aluminum Boats**



	Overal Length	:	16'/ 4.88m	Number of Chambers	:	5	Shaft Length	:20″/50.8cm
S	Overal Beam	:	7′/ 2.14m	Person Capacity	:	10	RDC Design Category	: C
ш	Inside Length	:	12'8"/3.85m	Weight	:	480lb/218kg		
S P	Inside Beam	:	3′6″/ 1.08m	Recommended HP	:	50hp /37.3kw		
	Tube Diameter	:	21″/ 0.53m	Maximum HP	:	60hp / 44.8kw		

- Marine Grade Aluminum Hull Shallow Water Version
- Stringer System Welded Under Aluminum Deck
- Life Line Around Tube Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves

Bow Step with Fold Down Stainless Steel Cleat

Customized Aluminum Consoles & Seats Upon Request

Lateral Fold Down Stainless Steel Cleat

Fiberglass Console with Forward Seat

Drain Scuppers

Tube Chaps

Boat Cover

**Chock Set** 

Removable Rowing Seat

Fiberglass Console

Heavy Duty Transom Knee

ND പ ന

ЧЧ

ΔD

z⊢

 $\triangleleft \triangleleft$ 

⊢ш

SΨ

<u>ہ ר</u>

⊲ ш

ZĽ

0⊃

 $- \vdash$ 

 $\vdash \triangleleft$ 

ு ய

Оц

- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye
- 4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
  Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric
- Double Solid Rub Rails
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves 1 Front & 5 Side Orca(CSM) Fabric Handles on Tubes

Paddles with Aluminum Shaft

3 Layer Reinforced Seams

Rubber Protector on Full Length of Keel

Paddle Holders

Maintenance Kit Owner's Manual

Hand Pump

- 6 Gal. Portable Fuel Tank Installed in Bow Locker
- Bench Seat with Storage

- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat
- Aluminum Console
- Aluminum Lean On