

Open FiberglassTenders



8VS

| | Overal Length | : | 8´6"/ 2.60m | Number of Chambers | : | 3 + 1 | Shaft Length | :15″/38.1cm |
|----|---------------|---|--------------|--------------------|---|--------------|---------------------|-------------|
| S | Overal Beam | • | 5´4"/ 1.64m | Person Capacity | : | 4 | RDC Design Category | : C |
| ш | Inside Length | : | 5´10″/ 1.79m | Weight | : | 125lb / 57kg | | |
| SP | Inside Beam | : | 2′4″/ 0.72m | Recommended HP | : | 8hp / 6.0kw | | |
| | Tube Diameter | : | 16″/ 0.40m | Maximum HP | : | 10hp / 7.5kw | | |

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat

ΩS

പ ന A R

 $\Box \supset$

z⊢

∢∢ ⊢ш

νт

<u>ہ ר</u>

⊲ш

ZĽ

0⊃

⊢∢ പപ Оц

- Diamond Shape Non Skid Deck

- Plastic External Transom Plate Aluminum Internal Transom Plate with Security Lip Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 Maintenance Kit

 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 Owner's Manual

 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor

 3 Layer Reinforced Seams
 Oarlock Bases

Hand Pump

Telescopic Oars with Aluminum Shaft
 Paddle Holders
 Removable Rowing Seat

- Tube Chaps
- Boat Cover
- Chock Set

- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat



Open FiberglassTenders



9VS

| | Overal Length | 9'6"/2.90m Number of Chambers : 3 + 1 Shaft Length : 15"/ | / 38.1cm |
|--------|---------------|---|----------|
| S | Overal Beam | 5'7"/ 1.72m Person Capacity : 4 RDC Design Category : C | |
| ш | Inside Length | 6´9″/ 2.06m Weight : 143lb / 65kg | |
| S P | Inside Beam | 2'8"/ 0.81m Recommended HP : 9.9hp / 7.4kw | |
| | Tube Diameter | 17"/ 0.43m Maximum HP : 15hp / 11.2kw | |

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat

ΩS

പ ന A R

 $\Box \supset$

z⊢

∢∢

⊢ш

νц

<u>ہ ب</u>

⊲ ш

Zĸ

0⊃

⊢∢ പപ Оц

- Diamond Shape Non Skid Deck
- Plastic External Transom Plate Aluminum Internal Transom Plate with Security Lip Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

- Raised Double Rub Rail Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- Deck Condensation Plug
 Removable Rowing Seat

 Deck Drain with Plug
 Hand Pump

 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 Maintenance Kit

 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 Owner's Manual

 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor

 3 Layer Reinforced Seams
 Oarlock Bases

Telescopic Oars with Aluminum Shaft
 Paddle Holders
 Removable Rowing Seat

- Tube Chaps
- Boat Cover
- Chock Set

- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat
- Bimini Top





10VS

Open FiberglassTenders



| | Overal Length | : 10′6″/ 3.19m | Number of Chambers | : 3 + 1 | Shaft Length | :15″/38.1cm |
|--------|---------------|---------------------------|--------------------|-----------------|---------------------|-------------|
| S | Overal Beam | : 5′7″/ 1.72m | Person Capacity | : 5 | RDC Design Category | : C |
| ш | Inside Length | · 7′7″/ 2.31m Yėrlis, | Weight | : 169lb / 77kg | | |
| S P | Inside Beam | Todos ୧୧୦/୧୫୫୦୦୦୦ a confo | rrRecognmended HP | : 15hp / 11.2kw | | |
| | Tube Diameter | Salu dø s/ 0.43m | Maximum HP | : 25hp / 18.7kw | | |

4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat

ΩS

പ ЧЧ

z⊢

 $\triangleleft \triangleleft$

μш

νт

<u>ں ح</u>

⊲ ш

Zĸ

0⊃

 \vdash

- ∢

പപ Оц

- Diamond Shape Non - Skid Deck

- Plastic External Transom Plate Aluminum Internal Transom Plate with Security Lip Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail Stainless Steel Bow Eye

- 3 Layer Reinforced Seams Oarlock Bases

- Telescopic Oars with Aluminum Shaft
 Paddle Holders
 Removable Rowing Seat

- Deck Orderisation Flug Flug Deck Drain with Plug Handles on Tubes Handles on Tubes Maintenance Kit 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes Owner's Manual 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes Additional Air Retaining Chamber Under the Floor

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat

- Removable Stern Seat
- Bimini Top
- Fiberglass Console
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit





12VS

Open FiberglassTenders



| | Overal Length | : 12′/ 3.66m | Number of Chambers | : 3+1 | Shaft Length Option 1: 15"/ 38.1cm |
|--------|---------------|---------------|--------------------|-----------------|--------------------------------------|
| S | Overal Beam | : 6′/1.82m | Person Capacity | : 6 | Shaft Length Option 2 : 20" / 50.8cm |
| ш | Inside Length | : 8′9″/ 2.67m | Weight | : 202lb / 92kg | RDC Design Category : C |
| S P | Inside Beam | : 2′9″/ 0.84m | Recommended HP | : 20hp / 14.9kw | |
| | Tube Diameter | : 18″/ 0.46m | Maximum HP | : 30hp / 22.4kw | |

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat

ΩS

പ ന

A R

 $\Box \supset$

zμ

⋖⋖ ーш

чг

<u>ہ ب</u>

⊲ ш

ZĽ

o⊃

 $\vdash \triangleleft$

ு ய

Оц

- Diamond Shape Non Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail
- Stainless Steal Bow Eye

- 4 Stainless Steal Davit Lifting Points
- Stainless Steal Towing Rings & Tie Downs Deck Condensation Plug

- Paddle Holders
- -Removable Stern Seat Hand Pump
- Maintenance Kit Owner's Manual
- Additional Air Retaining Chamber Under the Floor

- Bow Hatch Cushion
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steal Cleat
- Lateral Fold Down Stainless Steal Cleat

- Removable Rowing Seat
- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steal Helm Unit



- Deck Condensation Flug Deck Drain with Plug 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes 3 Layer Reinforced Seams Deckle with Alumitation Staff. Paddle with Aluminum Shaft



13VS

Open FiberglassTenders



| | Overal Length | : | 13′/ 3.96m | Number of Chambers | : | 3 + 1 | Shaft Length | :20″/50.8cm |
|--------|---------------|---|-------------|--------------------|---|---------------|---------------------|-------------|
| S | Overal Beam | : | 6′4″/ 1.94m | Person Capacity | : | 7 | RDC Design Category | : C |
| ш | Inside Length | : | 9′9″/ 2.97m | Weight | : | 293lb / 133kg | | |
| S P | Inside Beam | : | 3´1″/ 0.94m | Recommended HP | : | 30hp / 22.4kw | | |
| | Tube Diameter | : | 18″/ 0.46m | Maximum HP | : | 40hp / 29.8kw | | |

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hu
- Stringer System Laminated into Hull Bow Locker/ Seat

ND

പ

A R

 $\Box \supset$

z⊢

 $\triangleleft \triangleleft$

μш

νщ

പഗ

∢ш

ZĽ

0⊃

⊢∢

പപ Оц

—

- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate

- Aluminum Internal Transom Plate Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Raised Double Rub Rail Stainless Steel Bow Eye

Bow Hatch Cushion

Removable Rowing Seat

Boat Cover

Chock Set

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- Deck Oridensator Frug Deck Drain with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft Paddle Holders

Bimini Top

Fiberglass Console

Removable Stern SeatHand PumpMaintenance Kit

Owner's Manual

Additional Air Retaining Chamber Under the Floor

- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit





14VS

Open FiberglassTenders



| | Overal Length | : | 14′/ 4.27m | Number of Chambers | : | 4 + 1 | Shaft Length | :20″/50.8cm |
|--------|---------------|---|---------------|--------------------|---|---------------|---------------------|-------------|
| S O | Overal Beam | : | 6′4″/ 1.94m | Person Capacity | : | 8 | RDC Design Category | : С |
| Ш | Inside Length | : | 10′10″/ 3.30m | Weight | : | 348lb / 158kg | | |
| S P | Inside Beam | : | 3´1″/ 0.94m | Recommended HP | : | 40hp / 29.8kw | | |
| | Tube Diameter | : | 19″/ 0.48m | Maximum HP | : | 50hp / 37.3kw | | |

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat
- Diamond Shape Non Skid Deck

ΩS

പ A R

 $\Box \supset$

z⊢

A A

⊢ш

ωщ

с N

∢ш

ZĽ

0⊃

—

. ⊲

പപ Оц

- Aluminum Internal Transom Plate Aluminum Internal Transom Plate Orca (CSM) Five Layer Coated Fabric 4 Push Plastic Non-Corrosive 2 Stage Inflation Valves

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Raised Double Rub Rail Stainless Steel Bow Eye

Bow Hatch Cushion

Removable Rowing Seat

Boat Cover

Chock Set

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- Deck Originality Flug Deck Drain with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Sets of 3 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft Paddle Holders

- Bimini Top
- Fiberglass Console

Removable Stern SeatHand Pump

Maintenance Kit

Owner's Manual

Fiberglass Console with Forward Seat

Additional Air Retaining Chamber Under the Floor

- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit





15VS

Open FiberglassTenders



- Hand Laid Fiberglass Deep "V" Hull

ΔS

പ

A R

Z⊦

4 4

μш

νц

N L

⊲ ш

Zœ

o⊃

L

` ⊲ `

പ

Оц

- Stringer System Laminated into Hull Bow Locker/ Seat Diamond Shape Non Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Orca (CSM) Five Layer Coated Fabric 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

- Raised Double Solid Rub Rail
- Stainless Steel Bow Eye

Fuel Tank

Boat Cover

Chock Set

4 Stainless Steel Davit Lifting Points Stainless Steel Towing Rings & Tie Downs

- 2 Deck Drains with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of 4 Orca (CSM) Fabric Handles on Tubes
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams Paddle with Aluminum Shaft

 - Paddle Holders
 - Hand Pump

Bimini Top

Fiberglass Console

Maintenance Kit

Owner's Manual

- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

Removable Rowing Seat





17VS

Open FiberglassTenders



| | Overal Length | : | 17′/ 5.18m | Number of Chambers | : | 5 | Shaft Length | :20″/50.8cm |
|-----|---------------|---|--------------|--------------------|---|---------------|---------------------|-------------|
| S | Overal Beam | : | 8´1"/ 2.46m | Person Capacity | : | 15 | RDC Design Category | : C |
| Ш | Inside Length | : | 13´1"/ 4.00m | Weight | : | 772lb / 350kg | | |
| S P | Inside Beam | : | 4′4″/ 1.33m | Recommended HP | : | 75hp / 56kw | | |
| | Tube Diameter | : | 20″/ 0.50m | Maximum HP | : | 90hp / 67kw | | |

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull Bow Locker/ Seat Diamond Shape Non Skid Deck Plastic External Transom Plate

ND

പ

A R

z⊢

⋖⋖

⊢ш

чг

л v

∢ш

Zĸ

o⊃

⊢∢

പപ

Оц

 \vdash

- Aluminum Internal Transom Plate Orca (CSM) Five Layer Coated Fabric 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves Raised Double Solid Rub Rail

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

- Stainless Steel Bow Eye

Bow Hatch Cushion

Removable Rowing Seat

Fuel Tank

Boat Cover

Chock Set

- 4 Stainless Steel Davit Lifting Points

- 2 Inside Bow Sets of 3 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern of 3 Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams Paddle with Aluminum Shaft

Bimini Top

Maintenance KitOwner's Manual

- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

- 2 Deck Drains with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes

- Paddle Holders
- Hand Pump



19VS

Open FiberglassTenders



| | Overal Length | : | 19′/ 5.79m | Number of Chambers | : | 5 | Shaft Length | :25″/63.5cm |
|--------|---------------|---|--------------|--------------------|---|-----------------|---------------------|-------------|
| S | Overal Beam | : | 8′4″/ 2.53m | Person Capacity | : | 15 | RDC Design Category | : С |
| ш | Inside Length | : | 15´2″/ 4.62m | Weight | : | 1157lb / 526kg | | |
| S P | Inside Beam | : | 4´1"/ 1.25m | Recommended HP | : | 115hp / 85.8kw | | |
| | Tube Diameter | : | 22″/ 0.56m | Maximum HP | : | 150hp / 111.9kw | | |

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hu
- Stringer System Laminated into Hull Bow Locker/ Seat

ND

പ

ЧЧ

z⊢

 $\triangleleft \triangleleft$

μш

νт

<u>ہ ר</u>

∢ш

ZĽ

0⊃

ΓA

ு ய

Оц

- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate

- Aluminum Internal Transom Plate Orca (CSM) Five Layer Coated Fabric 4 Push Plastic Non-Corosive 2 Stage Inflation Valves

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Raised Double Solid Rub Rail Stainless Steel Bow Eye

Fuel Tank

Boat Cover

Chock Set

Bow Hatch Cushion

Removable Rowing Seat

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- 2 Deck Drains with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
 - 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft Paddle Holders

- Hand PumpMaintenance KitOwner's Manual
- Deck Storage

- Bimini Top Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit