lammina

10AL SUPERLIGHT

Aluminum Tenders



ے S **Overal Length** 10'6"/3.19m Number of Chambers : 3 Maximum HP : 20hp / 14.9kw **Overal Beam Person Capacity** : 5 : 5'6"/ 1.68m Shaft Length : 15" / 38.1cm Inside Length Weight : 117lb / 53kg : 7'6"/ 2.30m RDC Design Category : C Inside Beam : 2'8"/ 0.81m Weight with Bow Locker: 130lb/59kg Tube Diameter : 17"/ 0.43m Recommended HP : 10hp / 7.5kw

2 ж ш A A ∢ ∢ μш SH

⋖

Δш

0 н

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Deck Drain with Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat

- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- **Tube Chaps**
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat

- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bench Seat with Storage

