

ventus

Lightweight Fiberglass Tender

OPTIONAL BOW STEP

				The second secon			
	Overal Length	:	10′6″/ 3.19m	Number of Chambers	: 3+1	Shaft Length	:15″/38.1cm
E C S	Overal Beam	:	5′7″/ 1.72m	Person Capacity	: 5	RDC Design Category	: C
	Inside Length	:	7′7″/ 2.31m	Weight	: 123lb / 56kg		
S P	Inside Beam	:	2′8″/ 0.81m	Recommended HP	: 15hp / 11.2kw		
	Tube Diameter	:	17″/ 0.43m	Maximum HP	: 25hp / 18.7kw		

10VL

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Non Skid Rubber Floor Pannels

- Plastic External Transom Plate
- Plastic External Plate
 Aluminum Internal Transom Plate with Security Lip
 Stainless Steel Bow Eye
 Stainless Steel 3 Davit Lifting Points
 Inner Hull Drain with Plug

- Deck Condensation Plug
- Orca(CSM) Five Layer Coated Fabric

Removable Rowing Seat

- Raised Single Rub Rail
- Naised Single Rub Rain
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Hand Pump
 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
 2 Inside Stern Set of 2 Orca(CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor
- Oarlock Bases
 Telescopic Oars with Aluminum Shaft
 Paddle Holders

- 3 Layer Reinforced Seams

л г ⊲ ш Zĸ 0⊃

 \vdash

- ∢ പപ Ош

ΔS പ ന

ЧЧ

 $\Box \supset$

zμ < < ーш

мщ

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat

