lammina

14AL SUPERLIGHT

Aluminum Tenders



ے

S

2 ж ш A A ∢ ∢ \vdash \sqcup SH

 \circ

Δш

0 н

⋖

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye

Overal Beam

Inside Length

Inside Beam

Tube Diameter

- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings

Person Capacity

Recommended HP

Weight

- Deck Drain with Plug
 Orca(CSM) Five Layer Coated Fabric
 Raised Double Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

: 8

: 246lb/112kg

: 40hp/29.8kw

- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- $2\ Inside\ Bow\ Sets\ of\ Triple\ Orca(CSM)\ Fabric\ Handles\ on\ Tubes$

Weight with Bow Locker: 264lb/120kg

- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit

Shaft Length

RDC Design Category : C

: 20" / 50.8cm

- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings

: 6'7"/ 2.00m

: 10'10"/3.30m

: 3'3"/ 0.99m

: 19"/ 0.48m

- Tube Chaps
- Boat Cover
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Fiberglass Console
- Fiberglass Console with Forward Seat

- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit

