



| | | | | | | |
|-----------|----------------|-----------------|--------------------|----------------|-------------------------|----------------|
| S P E C S | Overall Length | : 8'6" / 2.60m | Number of Chambers | : 3 + 1 | Shaft Length | : 15" / 38.1cm |
| | Overall Beam | : 5'4" / 1.64m | Person Capacity | : 4 | RDC Design Category : C | |
| | Inside Length | : 5'10" / 1.79m | Weight | : 125lb / 57kg | | |
| | Inside Beam | : 2'4" / 0.72m | Recommended HP | : 8hp / 6.0kw | | |
| | Tube Diameter | : 16" / 0.41m | Maximum HP | : 10hp / 7.5kw | | |

| | | | | | | |
|------------------------------------|--|--|--|---|--|--|
| S T A N D A R D F E A T U R E S | <ul style="list-style-type: none">■ Hand Laid Fiberglass Deep "V" Hull■ Stringer System Laminated into Hull■ Bow Locker/ Seat■ Diamond Shape Non - Skid Deck■ Plastic External Transom Plate■ Aluminum Internal Transom Plate with Security Lip■ Orca (CSM) Five Layer Coated Fabric■ 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ Raised Solid Single Rub Rail■ Stainless Steel Bow Eye | | | <ul style="list-style-type: none">■ 4 Stainless Steel Davit Lifting Points■ Stainless Steel Towing Rings & Tie Downs■ Deck Condensation Plug■ Deck Drain with Plug■ 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes■ 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes■ 3 Layer Reinforced Seams■ Oarlock Bases | | |
| | | | | <ul style="list-style-type: none">■ Telescopic Oars with Aluminum Shaft■ Paddle Holders■ Removable Rowing Seat■ Hand Pump■ Maintenance Kit■ Owner's Manual■ Additional Air Retaining Chamber Under the Floor | | |

| | | | | | | |
|------------------------------------|---|--|--|---|--|--|
| O P T I O N A L F E A T U R E S | <ul style="list-style-type: none">■ Bow Hatch Cushion■ Tube Chaps■ Boat Cover■ Chock Set | | | <ul style="list-style-type: none">■ Bow Step with Fold Down Stainless Steel Cleat■ Lateral Fold Down Stainless Steel Cleat | | |
| | | | | | | |