navigo

9VS

Open FiberglassTenders





Overal Length	: 9′6″/ 2.90m	Number of Chambers	: 3+1	Shaft Length : 15" / 38.1cm
Overal Beam	: 5′7″/ 1.72m	Person Capacity	: 4	RDC Design Category : C
Inside Length	: 6′9″/ 2.06m	Weight	: 143lb / 65kg	
Inside Beam	: 2′8″/ 0.81m	Recommended HP	: 9.9hp / 7.4kw	
Tube Diameter	: 17"/ 0.43m	Maximum HP	: 15hp / 11.2kw	

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull Bow Locker/ Seat with Vent
- Bow Locker Storage to Fit a 6 Gal Portable Fuel Tank
- Diamond Shape Non Skid Deck

- Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
 Orca (CSM) Five Layer Coated Fabric
 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Raised Single Solid Rub Rail
 Stainless Stag
- Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 2 Inside Stern 1 Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams Oarlock Bases

- Telescopic Oars with Aluminum Shaft
 Paddle Holders
 Removable Rowing Seat

- Hand Pump
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor Hidden Channel for Fuel Fittings with SS Starburst

- Portable 6 gal Fuel Tank Installed in Bow Locker with Fittings
- Bow Hatch Cushion
- Tube Chaps
- Boat Cover
- Chock Set

- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat
- Bimini Top



 \forall

 \vdash \sqcup SH

ے S