

Profile F

F 15

Professional Fiberglass Boats



|                       |                |                 |                    |                 |                         |                   |
|-----------------------|----------------|-----------------|--------------------|-----------------|-------------------------|-------------------|
| S<br>P<br>E<br>C<br>S | Overall Length | : 15' / 4.57m   | Number of Chambers | : 5             | Shaft Length            | : 20" / 50.8cm    |
|                       | Overall Beam   | : 6'6" / 1.99m  | Person Capacity    | : 11            | Optional Fuel Tank      | : 23 Gal / 87 Lt. |
|                       | Inside Length  | : 11'6" / 3.50m | Weight             | : 484lb / 220kg | RDC Design Category : C |                   |
|                       | Inside Beam    | : 3'2" / 0.97m  | Recommended HP     | : 60hp / 44.8kw |                         |                   |
|                       | Tube Diameter  | : 19" / 0.48m   | Maximum HP         | : 75hp / 56kw   |                         |                   |

|  |   |  |  |  |  |  |
|--|---|--|--|--|--|--|
| S<br>T<br>A<br>N<br>D<br>A<br>R<br>D<br>F<br>E<br>A<br>T<br>U<br>R<br>E<br>S | <ul style="list-style-type: none"><li>Professional Grade Hand Laid Fiberglass Deep "V" Hull</li><li>Stringer System Laminated into Hull</li><li>Bow Locker/ Seat</li><li>Diamond Shape Non - Skid Deck</li><li>Plastic External Transom Plate</li><li>Aluminum Internal Transom Plate</li><li>Heavy Duty 1670 Decitex Orca (CSM) Five Layer Coated Fabric</li><li>Life Line Around Tube</li><li>Non - Skid (CSM) Coated Fabric on Tube's Surface</li><li>Pressure Relief Valves</li></ul> |  |  | <ul style="list-style-type: none"><li>4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves</li><li>Double Solid Rub Rail</li><li>Stainless Steel Bow Eye</li><li>4 Stainless Steel Davit Lifting Points</li><li>Stainless Steel Towing Rings &amp; Tie Downs</li><li>Deck Condensation Plug</li><li>Deck Drain with Plug</li><li>1 Front &amp; 5 Side Orca (CSM) Fabric Handles on Tubes</li><li>3 Layer Reinforced Seams</li><li>Paddle with Aluminum Shaft</li></ul> |  |  |
|  |   |  |  | <ul style="list-style-type: none"><li>Paddle Holders</li><li>Hand Pump</li><li>Maintenance Kit</li><li>Owner's Manual</li><li>Additional Air Retaining Chamber Under the Floor</li><li>Drain Scuppers</li><li>Rubber Protector on Full Length of Keel</li></ul>  |  |  |

|  |   |  |  |   |  |  |
|--|---|--|--|---|--|--|
| O<br>P<br>T<br>I<br>O<br>N<br>A<br>L<br>F<br>E<br>A<br>T<br>U<br>R<br>E<br>S | <ul style="list-style-type: none"><li>Optional Fuel Tank 23 Gal / 87 L</li><li>Bow Hatch Cushion</li><li>Boat Cover</li><li>Chock Set</li><li>Bow Step with Fold Down Stainless Steel Cleat</li><li>Lateral Fold Down Stainless Steel Cleat</li><li>Removable Rowing Seat</li></ul> |  |  | <ul style="list-style-type: none"><li>Bimini Top</li><li>Fiberglass Console</li><li>Fiberglass Console with Forward Seat</li><li>Bench Seat with Storage</li><li>Two person Jockey Seat</li><li>Stainless Steel Helm Unit</li></ul> |  |  |
|  |   |  |  |   |  |  |