



SPECS

Overall Length	: 7' 10" / 2.39m	Number of Chambers	: 2	Shaft Length	: 15" / 38.1cm
Overall Beam	: 4' 11" / 1.50m	Person Capacity	: 3	RDC Design Category	: C
Inside Length	: 5' 5" / 1.65m	Weight	: 66lb / 30kg		
Inside Beam	: 2' 2" / 0.66m	Recommended HP	: 3hp / 2.2kw		
Tube Diameter	: 16" / 0.41m	Maximum HP	: 4hp / 2.9kw		

STANDARDS  
FEATURES

- Shallow "V" Marine Grade Aluminum Hull
  - Non-Skid Rubber Floor Panels
  - Plastic External Transom Plate
  - Aluminum Internal Transom Plate With Security Lip
  - Aluminum Bow Eye
  - 3 Aluminum Davit Lifting Points
  - Aluminum Bow Towing Rings
  - Deck Drain with Plug
  - Orca (CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
  - Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
  - 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
  - 2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes
  - 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
  - Removable Rowing Seat
  - Oarlock Bases
  - Telescopic Oars with Aluminum Shaft
- Paddle Holders
  - Hand Pump
  - Maintenance Kit
  - Owner's Manual
  - 3 Layer Reinforced Seams

OPTIONAL  
FEATURES


- Tube Chaps
- Boat Cover
- Chock Set



lammina

8UL

Ultra Light Aluminum Tenders



S P E C S	Overall Length	: 8' 5" / 2.56m	Number of Chambers	: 2	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 4' 11" / 1.50m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	: 5' 10" / 1.79m	Weight	: 68lb / 31kg		
	Inside Beam	: 2' 2" / 0.66m	Recommended HP	: 4hp / 3.0kw		
	Tube Diameter	: 16" / 0.41m	Maximum HP	: 5hp / 3.8kw		

S T A N D A R D F E A T U R E S	<ul style="list-style-type: none"><li>Shallow "V" Marine Grade Aluminum Hull</li><li>Non-Skid Rubber Floor Panels</li><li>Plastic External Transom Plate</li><li>Aluminum Internal Transom Plate With Security Lip</li><li>Aluminum Bow Eye</li><li>3 Aluminum Davit Lifting Points</li><li>Aluminum Bow Towing Rings</li><li>Deck Drain with Plug</li><li>Orca (CSM) Five Layer Coated Fabric</li></ul>	<ul style="list-style-type: none"><li>Raised Single Rub Rail</li><li>Push Push Plastic Non-Corrosive 2 Stage Inflation Valves</li><li>1 Front &amp; 2 Side Orca (CSM) Fabric Handles on Tubes</li><li>2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes</li><li>2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes</li><li>Removable Rowing Seat</li><li>Oarlock Bases</li><li>Telescopic Oars with Aluminum Shaft</li></ul>	<ul style="list-style-type: none"><li>Paddle Holders</li><li>Hand Pump</li><li>Maintenance Kit</li><li>Owner's Manual</li><li>3 Layer Reinforced Seams</li></ul>

O P T I O N A L F E A T U R E S	<ul style="list-style-type: none"><li>Tube Chaps</li><li>Boat Cover</li><li>Chock Set</li></ul>	



lammina

9UL

Ultra Light Aluminum Tenders



S P E C S	Overall Length	: 9'1" / 2.76m	Number of Chambers	: 2	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 4'11" / 1.50m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	: 6'3" / 1.90m	Weight	: 75lb / 34kg		
	Inside Beam	: 2'3" / 0.70m	Recommended HP	: 8hp / 6kw		
	Tube Diameter	: 16" / 0.41m	Maximum HP	: 10hp / 7.5kw		

STANDARD FEATURES	<div><div><div>■ Shallow "V" Marine Grade Aluminum Hull</div><div>■ Non-Skid Rubber Floor Panels</div><div>■ Plastic External Transom Plate</div><div>■ Aluminum Internal Transom Plate With Security Lip</div><div>■ Aluminum Bow Eye</div><div>■ 3 Aluminum Davit Lifting Points</div><div>■ Aluminum Bow Towing Rings</div><div>■ Deck Drain with Plug</div><div>■ Orca (CSM) Five Layer Coated Fabric</div></div><div><div>■ Raised Single Rub Rail</div><div>■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves</div><div>■ 1 Front &amp; Side Orca (CSM) Fabric Handles on Tubes</div><div>■ 2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes</div><div>■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes</div><div>■ Removable Rowing Seat</div><div>■ Oarlock Bases</div><div>■ Telescopic Oars with Aluminum Shaft</div></div><div><div>■ Paddle Holders</div><div>■ Hand Pump</div><div>■ Maintenance Kit</div><div>■ Owner's Manual</div><div>■ 3 Layer Reinforced Seams</div></div></div>
-------------------	--

OPTIONAL FEATURES	<div><div>■ Tube Chaps</div><div>■ Boat Cover</div><div>■ Chock Set</div></div>
-------------------	---

lammina

10UL

Ultra Light Aluminum Tenders



S P E C S	Overall Length	: 10' / 3.05m	Number of Chambers	: 3	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 5'6" / 1.68m	Person Capacity	: 5	RDC Design Category	: C
	Inside Length	: 7'2" / 2.18m	Weight	: 95lb / 43kg		
	Inside Beam	: 2'8" / 0.81m	Recommended HP	: 9.9hp / 7.4kw		
	Tube Diameter	: 17" / 0.43m	Maximum HP	: 15hp / 11.2kw		

STANDARDS  
FEATURES

- Shallow "V" Marine Grade Aluminum Hull
- Transom Knee
- Non-Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate With Security Lip
- Aluminum Bow Eye
- 3 Aluminum Davit Lifting Points
- Aluminum Bow Towing Rings
- Deck Drain with Plug

- Orca (CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca (CSM) Fabric Handles on Tubes
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases

- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams

OPTIONAL  
FEATURES

- Tube Chaps
- Boat Cover
- Chock Set

