

Profile

A 15

SUPERLIGHT

Professional Aluminum Boats



	Overal Length	:	15'/ 4.57m	Number of Chambers	:	5	Maximum HP	: 60hp / 44.8kw
SPECS	Overal Beam	:	6'9"/ 2.06m	Person Capacity	:	9	Shaft Length	:20″/50.8cm
	Inside Length	:	11′8″/3.55m	Weight	:	383lb/174kg	RDC Design Category	: C
	Inside Beam	:	3'4"/ 1.03m	Weight with Bow Locker	:	401lb/182kg		
	Tube Diameter	:	19″/ 0.48m	Recommended HP	:	50hp /37.3kw		

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
 Life Line Around Tube

ΔS сυ

ЧĽ

z⊢

 $\triangleleft \triangleleft$

⊢ш

ഗഥ

л г

∢ш

Zĸ

o⊃

- 4

ு ய

Оц

- Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye 4 Aluminum Davit Lifting Points Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug

- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- Hand Pump

Paddles with Aluminum Shaft

- Maintenance Kit
- Owner's Manual

Paddle Holders

- Rubber Protector on Full Length of Keel
- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat
- Customized Aluminum Consoles & Seats Upon Request



- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Aluminum Console
- Aluminum Lean On