Profile

A 13-S SUPERLIGHT Professional Shallow Water Aluminum Boats



ш

2 жш A A \Box $z \vdash$ ∢ ⋖ \vdash \sqcup SН

 \sim ΨЫ \sim \circ \vdash \triangleleft д ш

0 ц

Overal Length	:	13'/ 3.96m	Number of Chambers	:	3	Maximum HP	: 40hp / 29.8kw
Overal Beam	:	6′5″/ 1.96m	Person Capacity	:	7	Shaft Length	: 20" / 50.8cm
Inside Length	:	9′10″/ 3.00m	Weight	:	282lb/128kg	RDC Design Category	: C
Inside Beam	:	3′3″/ 0.99m	Weight with Bow Locke	r:	297lb/ 135kg		
Tube Diameter	:	18"/ 0.46m	Recommended HP	:	30hp /22.4kw		

- Marine Grade Aluminum Hull Shallow Water Version
 Stringer System Welded Under Aluminum Deck
 Life Line Around Tube

- Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Aluminum Internal Transom Plate

- Aluminum Bow Eye
 4 Aluminum Davit Lifting Points
 Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric 3 Layer Reinforced Seams
- Double Solid Rub Rails
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Rubber Protector on Full Length of Keel

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat
- Customized Aluminum Consoles & Seats Upon Request

- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Uni
- Aluminum Console
- Aluminum Lean On

