navigo

19VS

Open FiberglassTenders



Overal Length : 19′/ 5.79m Number of Chambers : 5 Shaft Length **Overal Beam Person Capacity** : 15 RDC Design Category : C : 8'4"/ 2.53m Inside Length : 15'2"/ 4.62m Weight : 1157lb / 526kg Inside Beam : 4'1"/ 1.25m Recommended HP : 115hp / 85.8kw

Maximum HP

 \vdash \sqcup SH

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull Bow Locker/ Seat

Tube Diameter

- Diamond Shape Non Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
 Orca (CSM) Five Layer Coated Fabric
 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

: 22"/ 0.56m

- Raised Double Solid Rub Rail Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- 2 Deck Ordins with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes

: 150hp / 111.9kw

- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft
- Paddle Holders

- Hand Pump
- Maintenance Kit Owner's Manual
- Deck Storage

- Fuel Tank
- Bow Hatch Cushion
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat

- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat

: 25" / 63.5cm

- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit



S