

Professional Fiberglass Boats



	Overal Length	:	14′/ 4.27m	Number of Chambers	:	4 + 1	Shaft Length	:20″/50.8cm
S P E C S	Overal Beam	•	6´4"/ 1.94m	Person Capacity	:	8	RDC Design Category	: C
	Inside Length	:	10´10"/ 3.30m	Weight	:	403lb / 183kg		
	Inside Beam	:	3´1″/ 0.94m	Recommended HP	:	40hp / 29.8kw		
	Tube Diameter	:	19"/ 0.48m	Maximum HP	:	50hp / 37.3kw		

- Professional Grade Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat

ΩS

പ

ЧЧ

z⊢

 $\triangleleft \triangleleft$

<u>ہ ר</u>

∢ш

Zĸ

0⊃

ΓA

ு ய Оц

 \vdash

- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate

Bow Hatch Cushion

Removable Rowing Seat

Boat Cover

Chock Set

- Aluminum Internal Transom Plate
- Heavy Duty 1670 Decitex Orca (CSM) Five Layer Coated Fabric
- μш мщ
 - Non Skid (CSM) Coated Fabric on Tube's Surface Pressure Relief Valves
- 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

 Paddle Holders
 - Double Solid Rub Rail Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Stainless Steel Towing Rings & Tie Downs
- Deck Condensation Plug
- Deck Ordensation Flug Deck Drain with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft

- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat



- - Bench Seat with Storage
 - Two person Jockey Seat
 - Stainless Steel Helm Unit

- - Removable Stern Seat Hand Pump

 - Maintenance Kit
 - Owner's Manual
 - Additional Air Retaining Chamber Under the Floor Drain Scuppers Rubber Protector on Full Length of Keel

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat