

- Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Removable Rowing Seat
- Oarlock Base with Oarlocks
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 820 Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber Under the Floor
- Solid Single Rub Rail
- Stainless Steel Tow Rings
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual



8VS dinghies

- Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	8' 6"	2.60 M
OVERALL BEAM	5' 4"	1.64 M
INSIDE LENGTH	5' 10"	1.79 M
INSIDE BEAM	2' 4"	0.72 M
TUBE DIAMETER	16″	0.41 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	4	4
WEIGHT	125 LBS	57 KG
MAXIMUM HP	10 HP	7.5 KW
SHAFT LENGTH	15"	38.1 CM
RDC DESIGN CATEGORY	С	С





- Stainless Steel Bow Eye
- Bow Locker Seat with Vent & Storage to Fit a 6 Gal Portable Fuel Tank
- Under Deck Channel For Fuel Line with SS Starburst
- 4 Stainless Steel Davit Lifting Points
- · Removable Rowing Seat
- Oarlock Base with Oar locks
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 820 Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber Under the Floor
- Solid Single Rub Rail
- Stainless Steel Tow Rings
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual





- Portable 6 Gal Fuel Tank Installed with Fittings in Bow Locker
- Fiberglass Console
- One Person Jockey Seat
- Bench Seat with Storage
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump

- Master Switch
- Fuel/Water Separator & Canister
- Bow Step with Stainless Steel Fold
 Down Cleat
- · Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Color Boat Customization
- Seadek ® Foam Teak (Grey or Mocca)

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	9' 6"	2.90 M
OVERALL BEAM	5' 7"	1.72 M
INSIDE LENGTH	6' 9"	2.06 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	4	4
WEIGHT	152 LBS	69 KG
MAXIMUM HP	15 HP	11.2 KW
SHAFT LENGTH	15"	38.1 CM
RDC DESIGN CATEGORY	С	С





- Stainless Steel Bow Eye
- Bow Locker Seat with Vent & Storage to Fit a 6 Gal Portable Fuel Tank
- Under Deck Channel For Fuel Line with SS Starburst
- 4 Stainless Steel Davit Lifting Points
- · Removable Rowing Seat
- Oarlock Base with Oar locks
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 820 Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber
 Under the Floor
- Solid Single Rub Rail
- Stainless Steel Tow Rings
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual





- Portable 6 Gal Fuel Tank Installed with Fittings in Bow Locker
- Fiberglass Console
- One Person Jockey Seat
- Bench Seat with Storage
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch

- Fuel/Water Separator & Canister
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	10' 6"	3.19 M
OVERALL BEAM	5' 7"	1.72 M
INSIDE LENGTH	7' 7"	2.31 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	5	5
WEIGHT	169 LBS	77 KG
MAXIMUM HP	25 HP	18.7 KW
SHAFT LENGTH	15″	38.1 CM
RDC DESIGN CATEGORY	С	С





- Stainless Steel Bow Eye
- Bow Locker Seat with Vent & Storage to Fit a 6 Gal Portable Fuel Tank
- Under Deck Channel For Fuel Line with SS Starburst
- 4 Stainless Steel Davit Lifting Points
- Removable Seat
- Paddles
- Reinforced Orca (CSM) Fabric Handles on Tubes
- Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber Under the Floor
- Solid Single Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual





- Portable 6 Gal Fuel Tank Installed with Fittings in Bow Locker
- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Bench Seat with Storage
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump

- Master Switch
- Fuel/Water Separator & Canister
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization
- Seadek
 Foam Teak (Grey or Mocca)

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	12'	3.66 M
OVERALL BEAM	6'	1.82 M
INSIDE LENGTH	8' 9"	2.67 M
INSIDE BEAM	2' 9"	0.84 M
TUBE DIAMETER	18″	0.46 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	6	6
WEIGHT	202 LBS	92 KG
MAXIMUM HP	30 HP	22.4 KW
SHAFT LENGTH	15" - 20"	38.1 - 50.8 CM
RDC DESIGN CATEGORY	С	С





- Stainless Steel Bow Eye
- Bow Locker Seat with Vent & Storage to Fit a 6 Gal Portable Fuel Tank
- Under Deck Channel For Fuel Line with SS Starburst
- 4 Stainless Steel Davit Lifting Points
- Paddles
- Reinforced Orca (CSM) Fabric Handles on Tubes
- Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber
 Under the Floor
- Solid Double Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual





- Portable 6 Gal Fuel Tank Installed with Fittings in Bow Locker
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Fiberglass Console with Lateral Seat
- One Person Jockey Seat
- Two Person Jockey Seat
- Bench Seat with Storage
- Mechanical Steering System
- Hydraulic Steering System
 - Standard Rigging From Factory
 - SS LED Navigation Light
 - All Around LED Anchor Light

- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	13'	3.96 M
OVERALL BEAM	6' 4"	1.94 M
INSIDE LENGTH	9' 9"	2.97 M
INSIDE BEAM	3' 1"	0.94 M
TUBE DIAMETER	18"	0.46 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	7	7
WEIGHT	293 LBS	133 KG
MAXIMUM HP	40 HP	29.8 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	С	С





- Stainless Steel Bow Eye
- Bow Locker Seat with Vent & Storage to Fit a 6 Gal Portable Fuel Tank
- Under Deck Channel For Fuel Line with SS Starburst
- 4 Stainless Steel Davit Lifting Points
- Paddles
- Reinforced Orca (CSM) Fabric Handles on Tubes
- Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber
 Under the Floor
- Solid Double Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual





- Portable 6 Gal Fuel Tank Installed with Fittings in Bow Locker
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Fiberglass Console with Lateral Seat
- One Person Jockey Seat
- Two Person Jockey Seat
- Bench Seat with Storage
- Mechanical Steering System
- Hydraulic Steering System
 - Standard Rigging From Factory
 - SS LED Navigation Light
 - All Around LED Anchor Light

- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	14'	4.27 M
OVERALL BEAM	6' 4"	1.94 M
INSIDE LENGTH	10' 10"	3.30 M
INSIDE BEAM	3' 1"	0.94 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	4+1	4+1
PERSON CAPACITY	8	8
WEIGHT	348 LBS	158 KG
MAXIMUM HP	50 HP	37.3 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	С	С





- Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Paddles
- Reinforced Orca (CSM) Fabric Handles on Tubes
- Orca (CSM) Coated Fabric
- Solid Double Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual





- Fiberglass Console
- Fiberglass Console with Forward Seat
- Fiberglass Console with Lateral Seat
- One Person Jockey Seat
- Two Person Jockey Seat
- Bench Seat with Storage
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch

- Fuel/Water Separator & Canister
- Integrated Fuel Tank
 - Bow Step with Stainless Steel Fold
 Down Cleat
 - Lateral Stainless Steel Fold Down Cleat
 - Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization
- Seadek
 Foam Teak (Grey or Mocca)

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	15'	4.57 M
OVERALL BEAM	6' 6"	1.99 M
INSIDE LENGTH	11'6"	3.50 M
INSIDE BEAM	3' 2"	0.97 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	11	11
WEIGHT	484 LBS	220 KG
MAXIMUM HP	75 HP	56 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	С	С





- Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Paddles
- Reinforced Orca (CSM) Fabric Handles on Tubes
- Orca (CSM) Coated Fabric
- Solid Double Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual



17VS DINGHIES



- Fiberglass Console
- Fiberglass Console with Forward Seat
- One Person Jockey Seat
- Two Person Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister

- Integrated Fuel Tank
- Bow Step with Stainless Steel Fold Down Cleat
- · Lateral Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization
- Seadek

 B Foam Teak (Grey or Mocca)

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	17'	5.18 M
OVERALL BEAM	8' 1"	2.46 M
INSIDE LENGTH	13' 1"	4.00 M
INSIDE BEAM	4' 4"	1.33 M
TUBE DIAMETER	20"	0.50 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	15	15
WEIGHT	772 LBS	350 KG
MAXIMUM HP	90 HP	67.0 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	С	С





19VS DINGHIES

STANDARD FEATURES

- Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Paddles
- Reinforced Orca (CSM) Fabric Handles on Tubes
- Orca (CSM) Coated Fabric
- Solid Double Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES-

- Fiberglass Console
- Fiberglass Console with Forward Seat
- One Person Jockey Seat
- Two Person Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump

- Master Switch
- Fuel/Water Separator & Canister

- Integrated Fuel Tank
- Bow Step with Stainless Steel Fold Down Cleat
- · Lateral Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Bimini Top
- Cover
- Bow Hatch Cushion
- Tube Chaps
- Chock Set
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	19'	5.79 M
OVERALL BEAM	8' 4"	2.53 M
INSIDE LENGTH	15' 2"	4.62 M
INSIDE BEAM	4'1"	1.25 M
TUBE DIAMETER	22"	0.56 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	15	15
WEIGHT	1157 LBS	526 KG
MAXIMUM HP	150 HP	111.9 KW
SHAFT LENGTH	25"	63.5 CM
RDC DESIGN CATEGORY	С	С

