



STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Davit Lifting Points
- Non-Skid (CSM) Coated Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layers Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
- Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
- Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
- Fiberglass or Aluminum Jockey Consoles
- Customized Aluminum Console and Seats
- Aluminum Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Color Boat Customization

SPECIFICATION

IMPERIAL

METRIC

OVERALL LENGTH	11' 6"	3.5 M
OVERALL BEAM	5' 7"	1.7 M
INSIDE LENGTH	8' 6"	2.6 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	6	6
WEIGHT	227 LBS	103 KG
WEIGHT WITH BOW LOCKER	247 LBS	112 KG
RECOMMENDED HP	20 HP	14.9 KW
MAXIMUM HP	30 HP	22.4 KW
SHAFT LENGTH	15"	38.1 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	6°	6°
ALUMINUM HULL THICKNESS	0.125 in	3.18 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM