

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
 - Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
 - Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
 - Fiberglass or Aluminum Jockey Consoles
 - Customized Aluminum Console and Seats
 - Aluminum Jockey Seat
 - Leaning Bolster
- Mechanical Steering System
 - Hydraulic Steering System
 - Standard Rigging From Factory
 - SS LED Navigation Light
 - All Around LED Anchor Light
 - Automatic Bilge Pump
 - Master Switch
 - Fuel/Water Separator & Canister
 - Sunbrella Fabric Boat Cover
 - Chock Set
 - Lifting Harness
 - Electronics Upon Request
 - Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	13'	3.96 M
OVERALL BEAM	6' 7"	2 M
INSIDE LENGTH	9' 10"	3 M
INSIDE BEAM	3' 3"	0.99 M
TUBE DIAMETER	18"	0.46 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	7	7
WEIGHT	278 LBS	126 KG
WEIGHT WITH BOW LOCKER	311 LBS	141 KG
RECOMMENDED HP	30 HP	22.4 KW
MAXIMUM HP	40 HP	29.8 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	18°	18°
ALUMINUM HULL THICKNESS	0.125 in	3.18 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM