



## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version
- Rubber Keel Protector
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Aluminum or Fiberglass Console with Plexiglass Windshield & Grab Rail
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Mechanical Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Portable Fuel Tank
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Master Switch

### SPECIFICATION

### IMPERIAL

### METRIC

OVERALL LENGTH	14'	4.27 M
OVERALL BEAM	6' 4"	1.94 M
INSIDE LENGTH	10' 10"	3.3 M
INSIDE BEAM	3' 1"	0.94 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	4+1	4+1
PERSON CAPACITY	8	8
WEIGHT	403 LBS*	183 KG*
RECOMMENDED HP	40 HP	29.8 KW
MAXIMUM HP	50 HP	37.3 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	20°	20°

(\*) Weight spec. applies for the open version



## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version
- Rubber Keel Protector
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Aluminum or Fiberglass Console with Plexiglass Windshield & Grab Rail
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Mechanical Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Integrated Aluminum Fuel Tank
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Master Switch

### SPECIFICATION

### IMPERIAL

### METRIC

OVERALL LENGTH	15'	4.57 M
OVERALL BEAM	6' 6"	1.99 M
INSIDE LENGTH	11' 6"	3.5 M
INSIDE BEAM	3' 2"	0.97 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	11	11
WEIGHT	484 LBS*	220 KG*
RECOMMENDED HP	60 HP	44.8 KW
MAXIMUM HP	75 HP	56 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	22°	22°
OPTIONAL FUEL BUILT-IN TANK	23 GAL	87 LT

\* EPA built-in fuel tank 7% capacity reduction approx.

(\*) Weight spec. applies for the open version



## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Aluminum or Fiberglass Console with Plexiglass Windshield & Grab Rail
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Mechanical Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Integrated Aluminum Fuel Tank
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Battery Charger (Subject to Country of Delivery)

### SPECIFICATION

### IMPERIAL

### METRIC

OVERALL LENGTH	17'	5.18 M
OVERALL BEAM	8' 1"	2.46 M
INSIDE LENGTH	13' 1"	4 M
INSIDE BEAM	4' 4"	1.33 M
TUBE DIAMETER	20"	0.50 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	15	15
WEIGHT	772 LBS*	350 KG*
RECOMMENDED HP	75 HP	56 KW
MAXIMUM HP	90 HP	67 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	19°	19°
OPTIONAL FUEL BUILT-IN TANK	34 GAL	128 LT

\* EPA built-in fuel tank 7% capacity reduction approx.

(\*) Weight spec. applies for the open version



## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Hydraulic Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Automatic Bilge Pump
- Master Switch
- Battery Charger (Subject to Country of Delivery)
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Fiberglass Console with Plexiglass Windshield and Grab Rail
- Leaning Bolster
- 3 Stainless Steel Fold Down Cleats
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

### SPECIFICATION

### IMPERIAL

### METRIC

OVERALL LENGTH	19'	5.79 M
OVERALL BEAM	8' 4"	2.53 M
INSIDE LENGTH	15' 2"	4.62 M
INSIDE BEAM	4' 1"	1.25 M
TUBE DIAMETER	22"	0.56 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	15	15
WEIGHT	1157 LBS	526 KG
RECOMMENDED HP	115 HP	85.8 KW
MAXIMUM HP	150 HP	111.9 KW
SHAFT LENGTH	25"	63.5 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	20°	20°
FUEL BUILT-IN TANK	44 GAL	167 LT

\* EPA built-in fuel tank 7% capacity reduction approx.



## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Hydraulic Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Automatic Bilge Pump
- Master Switch
- Battery Charger (Subject to Country of Delivery)
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Fiberglass Console with Plexiglass Windshield and Grab Rail
- Integrated Aluminum Fuel Tank
- Bow Step
- Leaning Bolster
- 3 Stainless Steel Fold Down Cleats
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

### SPECIFICATION

### IMPERIAL

### METRIC

OVERALL LENGTH	21' 4"	6.50 M
OVERALL BEAM	8' 10"	2.70 M
INSIDE LENGTH	17' 3"	5.25 M
INSIDE BEAM	4' 9"	1.44 M
TUBE DIAMETER	22"	0.56 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	20	20
WEIGHT	1642 LBS	745 KG
RECOMMENDED HP	150 HP	111.9 KW
MAXIMUM HP	225 HP	167.85 KW
SHAFT LENGTH	25"	63.5 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	21°	21°
FUEL BUILT-IN TANK	63 GAL	240 LT

\* EPA built-in fuel tank 7% capacity reduction approx.



## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Hydraulic Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Automatic Bilge Pump
- Master Switch
- Battery Charger (Subject to Country of Delivery)
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Fiberglass Console with Plexiglass Windshield and Grab Rail
- Integrated Aluminum Fuel Tank
- Bow Step
- Leaning Bolster
- 3 Stainless Steel Fold Down Cleats
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

### SPECIFICATION

### IMPERIAL

### METRIC

OVERALL LENGTH	24'	7.31 M
OVERALL BEAM	9' 3"	2.82 M
INSIDE LENGTH	19' 3"	5.87 M
INSIDE BEAM	5' 4"	1.64 M
TUBE DIAMETER	24"	0.61 M
NUMBER OF CHAMBERS	6	6
PERSON CAPACITY	20	20
WEIGHT	1980 LBS	900 KG
RECOMMENDED HP	150 HP	111.9 KW
MAXIMUM HP	250 HP	186.5 KW
SHAFT LENGTH - SINGLE ENGINE INSTALLATION	25"	63.5 CM
SHAFT LENGTH - TWIN ENGINE INSTALLATION	20"	50.8 CM
RDC DESIGN CATEGORY	B	B
DEADRISE	20°	20°
FUEL BUILT-IN TANK	65 GAL	246 LT

\* EPA built-in fuel tank 7% capacity reduction approx.





## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Hydraulic Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Automatic Bilge Pump
- Master Switch
- Battery Charger (Subject to Country of Delivery)
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Fiberglass Console with Plexiglass Windshield and Grab Rail
- Integrated Aluminum Fuel Tank
- Bow Step
- Leaning Bolster
- 3 Stainless Steel Fold Down Cleats
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	27'	8.23 M
OVERALL BEAM	10' 1"	3.07 M
INSIDE LENGTH	22' 11"	6.99 M
INSIDE BEAM	6' 4"	1.93 M
TUBE DIAMETER	24"	0.61 M
NUMBER OF CHAMBERS	6	6
PERSON CAPACITY	25	25
WEIGHT	2853 LBS	1297 KG
RECOMMENDED HP	250 HP	186.5 KW
MAXIMUM HP	500 HP	373 KW
SHAFT LENGTH - SINGLE ENGINE INSTALLATION	30"	76.2 CM
SHAFT LENGTH - TWIN ENGINE INSTALLATION	25"	63.5 CM
RDC DESIGN CATEGORY	B	B
DEADRISE	22°	22°
FUEL BUILT-IN TANK	189 GAL	715 LT
* EPA built-in fuel tank 7% capacity reduction approx.		