



STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version
- Rubber Keel Protector
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Aluminum or Fiberglass Console with Plexiglass Windshield & Grab Rail
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Mechanical Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Portable Fuel Tank
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Master Switch

SPECIFICATION

IMPERIAL

METRIC

OVERALL LENGTH	14'	4.27 M
OVERALL BEAM	6' 4"	1.94 M
INSIDE LENGTH	10' 10"	3.3 M
INSIDE BEAM	3' 1"	0.94 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	4+1	4+1
PERSON CAPACITY	8	8
WEIGHT	403 LBS*	183 KG*
RECOMMENDED HP	40 HP	29.8 KW
MAXIMUM HP	50 HP	37.3 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	20°	20°

(*) Weight spec. applies for the open version