



STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version
- Rubber Keel Protector
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Aluminum or Fiberglass Console with Plexiglass Windshield & Grab Rail
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Mechanical Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Integrated Aluminum Fuel Tank
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Master Switch

SPECIFICATION

IMPERIAL

METRIC

OVERALL LENGTH	15'	4.57 M
OVERALL BEAM	6' 6"	1.99 M
INSIDE LENGTH	11' 6"	3.5 M
INSIDE BEAM	3' 2"	0.97 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	11	11
WEIGHT	484 LBS*	220 KG*
RECOMMENDED HP	60 HP	44.8 KW
MAXIMUM HP	75 HP	56 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	22°	22°
OPTIONAL FUEL BUILT-IN TANK	27 GAL	102 LT

* EPA built-in fuel tank 7% capacity reduction approx.

(*) Weight spec. applies for the open version