



## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version
- Hand Pump
- Maintenance Kit
- Owner's Manual



## OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Aluminum or Fiberglass Console with Plexiglass Windshield & Grab Rail
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Mechanical Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Integrated Aluminum Fuel Tank
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Battery Charger (Subject to Country of Delivery)

### SPECIFICATION

### IMPERIAL

### METRIC

OVERALL LENGTH	17'	5.18 M
OVERALL BEAM	8' 1"	2.46 M
INSIDE LENGTH	13' 1"	4 M
INSIDE BEAM	4' 4"	1.33 M
TUBE DIAMETER	20"	0.50 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	15	15
WEIGHT	772 LBS*	350 KG*
RECOMMENDED HP	75 HP	56 KW
MAXIMUM HP	90 HP	67 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	19°	19°
OPTIONAL FUEL BUILT-IN TANK	34 GAL	128 LT

\* EPA built-in fuel tank 7% capacity reduction approx.

(\*) Weight spec. applies for the open version