



STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Hydraulic Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Automatic Bilge Pump
- Master Switch
- Battery Charger (Subject to Country of Delivery)
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Fiberglass Console with Plexiglass Windshield and Grab Rail
- Integrated Aluminum Fuel Tank
- Bow Step
- Leaning Bolster
- 3 Stainless Steel Fold Down Cleats
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

SPECIFICATION

IMPERIAL

METRIC

OVERALL LENGTH	21' 4"	6.50 M
OVERALL BEAM	8' 10"	2.70 M
INSIDE LENGTH	17' 3"	5.25 M
INSIDE BEAM	4' 9"	1.44 M
TUBE DIAMETER	22"	0.56 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	20	20
WEIGHT	1642 LBS	745 KG
RECOMMENDED HP	150 HP	111.9 KW
MAXIMUM HP	225 HP	167.85 KW
SHAFT LENGTH	25"	63.5 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	21°	21°
FUEL BUILT-IN TANK	63 GAL	240 LT

* EPA built-in fuel tank 7% capacity reduction approx.