



STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- Non-Skid Orca (CSM) Coated Fabric on Top of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Bow Locker
- Pressure Relief Valves
- Hydraulic Steering System
- SS LED Navigation Light
- All Around LED Anchor Light
- Standard Rigging From Factory
- Automatic Bilge Pump
- Master Swtich
- Battery Charger (Subject to Country of Delivery)
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Fiberglass Console with Plexiglass Windshield and Grab Rail
- Integrated Aluminum Fuel Tank
- Bow Step
- Leaning Bolster
- 3 Stainless Steel Fold Down Cleats
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles & Seats
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	27'	8.23 M
OVERALL BEAM	10' 1"	3.07 M
INSIDE LENGTH	22' 11"	6.99 M
INSIDE BEAM	6' 4"	1.93 M
TUBE DIAMETER	24"	0.61 M
NUMBER OF CHAMBERS	6	6
PERSON CAPACITY	25	25
WEIGHT	2853 LBS	1297 KG
RECOMMENDED HP	250 HP	186.5 KW
MAXIMUM HP	500 HP	373 KW
SHAFT LENGTH - SINGLE ENGINE INSTALLATION	30"	76.2 CM
SHAFT LENGTH - TWIN ENGINE INSTALLATION	25"	63.5 CM
RDC DESIGN CATEGORY	B	B
DEADRISE	22°	22°
FUEL BUILT-IN TANK	189 GAL	715 LT
* EPA built-in fuel tank 7% capacity reduction approx.		