

STANDARD FEATURES

- Stainless Steel Bow Eye
- 3 Stainless Steel Davit Lifting Points
- Removable Rowing Seat
- Oarlock Base with Oarlocks
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 820 Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber Under the Floor
- Single Rub Rail
- 3 Layers Reinforced Seams
- Non-Skid Rubber Floor Panels
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bimini Top
- Tube Chaps
- Chock Set
- Bow Step with Stainless Steel Fold Down Cleat
- Color Boat Customization
- Bow Bench Seat
- Lateral Stainless Steel Fold Down Cleat

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	8' 6"	2.60 M
OVERALL BEAM	5' 6"	1.68 M
INSIDE LENGTH	5' 10"	1.79 M
INSIDE BEAM	2' 4"	0.72 M
TUBE DIAMETER	16"	0.40 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	4	4
WEIGHT	95 LBS	43 KG
MAXIMUM HP	10 HP	7.5 KW
SHAFT LENGTH	15"	38.1 CM
RDC DESIGN CATEGORY	C	C

STANDARD FEATURES

- Stainless Steel Bow Eye
- 3 Stainless Steel Davit Lifting Points
- Removable Rowing Seat
- Oarlock Base with Oar locks
- Non-Skid Rubber Floor Panels
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 820 Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber Under the Floor
- Single Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bimini Top
- Cover
- Tube Chaps
- Chock Set
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Color Boat Customization
- Bow Bench Seat

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	9' 6"	2.90 M
OVERALL BEAM	5' 7"	1.72 M
INSIDE LENGTH	6' 9"	2.06 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	4	4
WEIGHT	106 LBS	48 KG
MAXIMUM HP	15 HP	11.2 KW
SHAFT LENGTH	15"	38.1 CM
RDC DESIGN CATEGORY	C	C

STANDARD FEATURES

- Stainless Steel Bow Eye
- 3 Stainless Steel Davit Lifting Points
- Removable Rowing Seat
- Oarlock Base with Oar locks
- Non-Skid Rubber Floor Panels
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 820 Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber Under the Floor
- Single Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bimini Top
- Cover
- Tube Chaps
- Chock Set
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Color Boat Customization
- Bow Bench Seat

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	10' 6"	3.19 M
OVERALL BEAM	5' 7"	1.72 M
INSIDE LENGTH	7' 7"	2.31 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	5	5
WEIGHT	123 LBS	56 KG
MAXIMUM HP	25 HP	18.7 KW
SHAFT LENGTH	15"	38.1 CM
RDC DESIGN CATEGORY	C	C

STANDARD FEATURES

- Stainless Steel Bow Eye
- 3 Stainless Steel Davit Lifting Points
- Removable Rowing Seat
- Non-Skid Rubber Floor Panels
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 820 Orca (CSM) Coated Fabric
- Additional Air Retaining Chamber Under the Floor
- Single Rub Rail
- 3 Layers Reinforced Seams
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bimini Top
- Cover
- Tube Chaps
- Chock Set
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Color Boat Customization
- Bow Bench Seat

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	12'	3.66 M
OVERALL BEAM	5' 10"	1.77 M
INSIDE LENGTH	8' 9"	2.67 M
INSIDE BEAM	2' 9"	0.84 M
TUBE DIAMETER	18"	0.46 M
NUMBER OF CHAMBERS	3+1	3+1
PERSON CAPACITY	6	6
WEIGHT	156 LBS	71 KG
MAXIMUM HP	30 HP	22.4 KW
SHAFT LENGTH	15"	38.1 CM
RDC DESIGN CATEGORY	C	C