

## STANDARD FEATURES

- Integrated Marine Grade Aluminum Fuel Tank (10-Gal)
- Diamond Non-Skid Deck
- Rear Seat with Ample Storage
- Fully Upholstered Seating - Spradling ®
- Console with Forward Seat
- Easy Port & Starboard Access
- Stainless Steel Port/Starboard Hand Rail
- Ample Engine Access
- Stainless Steel Bow Eye
- 2 Stern Stainless Steel Foldable Cleats
- 3 Stainless Steel Davit Lifting Points
- Stainless Steel Stern Ski-Eye & Stern Hand Rail
- Stainless Steel Transom Tie Downs
- Battery Box
- 2 Recessed Cup Holders
- Water Tight Engine Compartment Seal
- Orca ® (CSM) Coated Fabric
- Non-Corrosive Push-Push Inflation Valves
- Single Solid Rub Rail
- Reinforced External Seams
- Self-Bailing Deck System with Non-Return Valves
- Stainless Steel Drain Plugs
- Automatic Fire Extinguisher
- Safety Lanyard Switch
- Automatic 500 GPH Bilge Pump
- Removable Pole LED Navigation & Anchor Light
- Battery Switch
- Maintenance - Free Battery
- Engine Compartment In-Line Blower
- Sport Steering Wheel
- Steering System
- Complete Tin Wiring & (Head) Heat Shrink Seal Terminals
- Control Panel (Includes Fuel Gauge)
- Shift Control
- Stainless Steel Gas Springs for Engine Compartment
- Under Platform Sliding SS Ladder
- Hand Pump & Maintenance Kit
- Owner's Manual
- Rotax ® ACE 90 ECT
- Catalytic Exhaust System
- Muffler & Silencer
- 12 V DC Socket & USB-C Port



## OPTIONAL FEATURES

- Synthetic Teak
- Boat Cover
- Stereo System & Compass
- GPS Chart Plotter / Sounder
- Stainless Steel Tie Downs
- Quick Release Wheel
- Stainless Steel Anchor
- Name on Upholstery
- LED Courtesy Lights
- Battery Charger
- VHF & Antenna
- Upholstery and Inflatable Tube Color Option
- Adjustable Steering Wheel
- Fiberglass Bow Step with SS cleat and navigation lights

SPECIFICATION	US UNIT	METRIC
OVERALL LENGTH	9' 6"	2.90 M
OVERALL BEAM	5' 7"	1.70 M
HEIGHT	2' 8"	0.83 M
TUBE DIAMETER	16"	0.41 M
NUMBER OF CHAMBERS	4	4
PERSON CAPACITY	4	4
WEIGHT	683 LBS	310 KG
INSTALLED HP	90 HP	67,1 KW
RDC DESIGN CATEGORY	C	C
FUEL BUILT-IN TANK	10 GAL	38 LT

\* EPA built-in fuel tank 7% capacity reduction approx.