## **STANDARD** FFATURES

- Integrated Marine Grade Aluminum Fuel Tank (10-Gal)
- · Diamond Non-Skid Deck
- Rear Seat with Ample Storage
- Fully Upholstered Seating -Spradling ®
- · Console with Forward Seat
- Integrated Bow Locker
- Easy Port & Starboard Access
- Stainless Steel Port/Starboard Hand Rail
- Ample Engine Access
- Stainless Steel Bow Eye
- 2 Stern Stainless Steel Foldable Cleats
- 4 Stainless Steel Davit Lifting Points
- Stainless Steel Stern Ski-Eye & Stern Hand Rail
- · Stainless Steel Transom Tie Downs
- Battery Box
- 2 Recessed Cup Holders
- Water Tight Engine Compartment Seal
- · Orca ® (CSM) Coated Fabric
- Non-Corrosive Push-Push Inflation Valves
- Single Solid Rub Rail
- · Reinforced External Seams

- Orca ® (CSM) Fabric Handles on Tubes
- Self-Bailing Deck System with Non-Return Valves
- · Stainless Steel Drain Plugs
- Automatic Fire Extinguisher
- · Safety Lanyard Switch
- Automatic 500 GPH Bilge Pump
- Removable Pole LED Navigation & Anchor Light
- Battery Switch
- · Maintenance Free Battery
- · Engine Compartment In-Line Blower
- Sport Steering Wheel
- Steering System
- Complete Tin Wiring & (Head) Heat Shrink Seal Terminals
- Control Panel (Includes Fuel Gauge)
- Shift Control
- Stainless Steel Gas Springs for Engine Compartment
- Under Platform Sliding SS Ladder
- · Hand Pump & Maintenance Kit
- Owner's Manual
- Rotax ® ACE 90 ECT
- · Catalytic Exhaust System
- · Muffler & Silencer
- 12 V DC Socket & USB-C Port



## **OPTIONAL** FEATURES-

- Synthetic Teak
- Boat Cover
- Stereo System & Compass
- · GPS Chart Plotter / Sounder
- Stainless Steel Tie Downs
- Quick Release Wheel
- Stainless Steel Anchor
- Name on Upholstery
- · LED Courtesy Lights
- · Battery Charger

- VHF & Antenna
- Upholstery and Inflatable Tube Color Option
- Adjustable Steering Wheel
- Fiberglass Bow Step with SS cleat and navigation lights

SPECIFICATION	US UNIT	METRIC
OVERALL LENGTH	10' 10"	3.30 M
OVERALL BEAM	5′ 8″	1.72 M
HEIGHT	2' 9"	0.85 M
TUBE DIAMETER	16"	0.41 M
NUMBER OF CHAMBERS	4	4
PERSON CAPACITY	5	5
WEIGHT	728 LBS	330 KG
INSTALLED HP	90 HP	67,1 KW
RDC DESIGN CATEGORY	С	С
FUEL BUILT-IN TANK * EPA built-in fuel tank 7% capacity reduction approx.	10 GAL	38 LT

