

# ***PROFILE***



 **IAB**



***INVULNERABLE***

***PROFILE***



Our company was founded on a commitment to quality that guides us to this day. We are the only company in the world that manufactures its boats exclusively in-house, overseeing every aspect from start to finish, meeting or exceeding certified industry benchmarks and the standards for most globally recognized organizations. We keep meticulous records so there are never any surprises. Our ever-evolving quality-control measures ensure we always live up to our promise to build the best boats in the world.



# PROFILE F

PROFESSIONAL FIBERGLASS BOATS

PROFILE F 17


MILITARY GRADE ORCA (CSM) FABRIC | FIBERGLASS REINFORCED PROFESSIONAL GRADE HULL  
UNSURPASSED PERFORMANCE | OPEN AND SPACIOUS DESIGN | DEEP V HULL

## STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points (Except 21-28)
- Non-Skid Orca (CSM) Fabric On Top Of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Fabric
- Life Line Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version (14-17)
- Hydraulic Steering System (19-28)
- SS LED Navigation Light ( 19 - 28)
- All Around LED Anchor Light (19-28)
- Standard Rigging From Factory (19-28)
- Automatic Bilge Pump (19-28)
- Master Switch (19-28)
- Battery Charger (19-28 / Subject To Country Of Delivery)
- Fuel/Water Separator & Canister (19-28)
- Fuel Sending Unit (19-28)
- Fiberglass Console With Plexiglass Windshield & Grab Rail (19-28)
- Leaning Bolster (19-28)
- Integrated Aluminum Fuel Tank (19-28)
- Bow Step (19-28)
- 3 Stainless Steel Fold Down Cleats (19-28)
- Rubber Keel Protector (F 14 & F 15)
- Hand Pump
- Maintenance Kit
- Owner's Manual

## OPTIONAL FEATURES

- Fiberglass Or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles And Seats
- Mechanical Steering System (14-17)
- SS LED Navigation Light (14-17)
- All Around LED Anchor Light (14-17)
- Standard Rigging From Factory (14-17)
- Bow Step With Stainless Steel Fold Down Cleat (14-17)
- Lateral Stainless Steel Fold Down Cleat (14-17)
- Portable Fuel Tank (14)
- Integrated Aluminum Fuel Tank (15-17)
- Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Master Switch

| 7 MODELS<br>FROM 14 TO 28 FEET | F 14                                                                                 | F 15                                                                                 | F 17                                                                                 | F 19                                                                                 | F 21                                                                                 | F 24                                                                                 | F 28                                                                                 |
|--------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|                                |  |  |  |  |  |  |  |
| LENGTH                         | 14' (4.27 M)                                                                         | 15' (4.57 M)                                                                         | 17' (5.18 M)                                                                         | 19' (5.79 M)                                                                         | 21'4" (6.50 M)                                                                       | 24' (7.31 M)                                                                         | 27' (8.23 M)                                                                         |
| BEAM                           | 6'4" (1.94 M)                                                                        | 6'6" (1.99 M)                                                                        | 8'1" (2.46 M)                                                                        | 8'4" (2.53 M)                                                                        | 8'10" (2.70 M)                                                                       | 9'3" (2.82 M)                                                                        | 10'1" (3.07 M)                                                                       |
| INSIDE LENGTH                  | 10'10" (3.3 M)                                                                       | 11'6" (3.5 M)                                                                        | 13'1" (4 M)                                                                          | 15'2" (4.62 M)                                                                       | 17'3" (5.25 M)                                                                       | 19'3" (5.87 M)                                                                       | 22'11" (6.99 M)                                                                      |
| INSIDE BEAM                    | 3' 1" (0.94 M)                                                                       | 3'2" (0.97 M)                                                                        | 4'4" (1.33 M)                                                                        | 4'1" (1.25 M)                                                                        | 4'9" (1.44 M)                                                                        | 5'4" (1.64 M)                                                                        | 6'4" (1.93 M)                                                                        |
| TUBE DIAMETER                  | 19" (0.48 M)                                                                         | 19" (0.48 M)                                                                         | 20" (0.50 M)                                                                         | 22" (0.56 M)                                                                         | 22" (0.56 M)                                                                         | 24" (0.61 M)                                                                         | 24" (0.61 M)                                                                         |
| CAPACITY PERSONS               | 8                                                                                    | 11                                                                                   | 15                                                                                   | 15                                                                                   | 20                                                                                   | 20                                                                                   | 25                                                                                   |
| WEIGHT                         | 403* LBS (183* KG)                                                                   | 484* LBS (220* KG)                                                                   | 772* LBS (350* KG)                                                                   | 1157 LBS (526 KG)                                                                    | 1642 LBS (745 KG)                                                                    | 1980 LBS (900 KG)                                                                    | 2853 LBS (1297 KG)                                                                   |
| RECOMMENDED HP                 | 40                                                                                   | 60                                                                                   | 75                                                                                   | 115                                                                                  | 150                                                                                  | 150                                                                                  | 250                                                                                  |
| MAXIMUM HP                     | 50                                                                                   | 75                                                                                   | 90                                                                                   | 150                                                                                  | 225                                                                                  | 250                                                                                  | 500                                                                                  |

PROFILE



PROFESSIONAL ALUMINUM BOATS



PROFILE A 12






MILITARY GRADE ORCA (CSM) FABRIC | ALUMINUM REINFORCED PROFESSIONAL GRADE HULL  
DURABLE ENOUGH FOR ROCKY SHORES & CORAL REEFS | CUSTOM ACCESSORIES UPON REQUEST | DEEP V HULL

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top Of Tube
- Seadeck® Eva Foam Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Fabric
- Life Line Around Tube
- Hydraulic Steering System (18)
- SS Led Navigation Light (18)
- All Around Led Anchor Light (18)
- Standard Rigging From Factory (18)
- Aluminum Console With Plexiglass Windshield & Grab Rail (18)
- Leaning Bolster (18)
- Integrated Aluminum Fuel Tank (18)
- Fuel Sending Unit (18)
- Bow Locker (18)
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Bow Locker
- Portable Fuel Tank Installed In Bow Locker
- Aluminum Console
- Fiberglass Or Aluminum Jockey Consoles
- Customized Aluminum Consoles And Seats
- Aluminum Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around Led Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- T-Top (A 18)
- Light Arch (A 18)
- Engine Guard (A 18)
- Stern / Bow Towing Post (A 18)
- Color Boat Customization

| 7 MODELS<br>FROM 11 TO 18 FEET | A 11                                                                                 | A 12                                                                                 | A 13                                                                                 | A 14                                                                                 | A 15                                                                                 | A 16                                                                                 | A 18                                                                                 |
|--------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|                                |  |  |  |  |  |  |  |
| LENGTH                         | 11'6" (3.5 M)                                                                        | 12' (3.66 M)                                                                         | 13' (3.96 M)                                                                         | 14' (4.27 M)                                                                         | 15' (4.57 M)                                                                         | 16' (4.88 M)                                                                         | 18' (5.49 M)                                                                         |
| BEAM                           | 5'7" (1.7 M)                                                                         | 6'1" (1.85 M)                                                                        | 6'7" (2 M)                                                                           | 6'7" (2 M)                                                                           | 6'9" (2.06 M)                                                                        | 7' (2.14 M)                                                                          | 7'11" (2.40 M)                                                                       |
| INSIDE LENGTH                  | 8'6" (2.6 M)                                                                         | 8'10" (2.7 M)                                                                        | 9'10" (3 M)                                                                          | 10'10" (3.3 M)                                                                       | 11'8" (3.55 M)                                                                       | 13' 2" (3.85 M)                                                                      | 14'8" (4.47 M)                                                                       |
| INSIDE BEAM                    | 2'8" (0.81 M)                                                                        | 2'11" (0.89 M)                                                                       | 3'3" (0.99 M)                                                                        | 3'3" (0.99 M)                                                                        | 3'4" (1.03 M)                                                                        | 3'6" (1.08 M)                                                                        | 4'3" (1.30 M)                                                                        |
| TUBE DIAMETER                  | 17" (0.43 M)                                                                         | 17" (0.43 M)                                                                         | 18" (0.46 M)                                                                         | 19" (0.48 M)                                                                         | 19" (0.48 M)                                                                         | 21" (0.53 M)                                                                         | 21" (0.53 M)                                                                         |
| CAPACITY PERSONS               | 6                                                                                    | 6                                                                                    | 7                                                                                    | 8                                                                                    | 9                                                                                    | 10                                                                                   | 15                                                                                   |
| WEIGHT                         | 212 LBS (96 KG)                                                                      | 231 LBS (105 KG)                                                                     | 278 LBS (126 KG)                                                                     | 297 LBS (134 KG)                                                                     | 392 LBS (178 KG)                                                                     | 458 LBS (208 KG)                                                                     |                                                                                      |
| WEIGHT WITH BOW LOCKER         | 229 LBS (104 KG)                                                                     | 250 LBS (113 KG)                                                                     | 311 LBS (141 KG)                                                                     | 312 LBS (142 KG)                                                                     | 421 LBS (191 KG)                                                                     | 479 LBS (217 KG)                                                                     | 859 LBS (390 KG)                                                                     |
| RECOMMENDED HP                 | 20                                                                                   | 25                                                                                   | 30                                                                                   | 40                                                                                   | 50                                                                                   | 50                                                                                   | 90                                                                                   |
| MAXIMUM HP                     | 30                                                                                   | 30                                                                                   | 40                                                                                   | 50                                                                                   | 60                                                                                   | 70                                                                                   | 115                                                                                  |
| SHAFT LENGTH                   | 20" (50.8 CM)                                                                        | 20" (50.8 CM)                                                                        | 20" (50.8 CM)                                                                        | 20" (50.8 CM)                                                                        | 20" (50.8 CM)                                                                        | 20" (50.8 CM)                                                                        | 25" (63.5 CM)                                                                        |



PROFESSIONAL ALUMINUM SHALLOW WATER BOATS

PROFILE A 16-S



MILITARY GRADE ORCA (CSM) FABRIC | ALUMINUM REINFORCED PROFESSIONAL GRADE HULL  
DURABLE ENOUGH FOR ROCKY SHORES | SHALLOW WATER VERSION HULL | CUSTOM ACCESSORIES UPON REQUEST




STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top Of Tube

- Seadeck® Eva Foam Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Fabric
- Life Line Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Bow Locker
- Portable Fuel Tank Installed In Bow Locker
- Aluminum Console
- Fiberglass Or Aluminum Jockey Consoles
- Customized Aluminum Consoles And Seats
- Aluminum Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Color Boat Customization

| 5 MODELS<br>FROM 11 TO 16 FEET | A 11-S                                                                              | A 12-S                                                                              | A 13-S                                                                              | A 14-S                                                                              | A 16-S                                                                              |
|--------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                                |  |  |  |  |  |
| LENGTH                         | 11' 6" (3.5 M)                                                                      | 12' (3.66 M)                                                                        | 13' (3.96 M)                                                                        | 14' (4.27 M)                                                                        | 16' (4.88 M)                                                                        |
| BEAM                           | 5' 7" (1.7 M)                                                                       | 5' 11" (1.8 M)                                                                      | 6' 5" (1.96 M)                                                                      | 6' 5" (1.96 M)                                                                      | 7' (2.14 M)                                                                         |
| INSIDE LENGTH                  | 8' 6" (2.6 M)                                                                       | 8' 10" (2.7 M)                                                                      | 9' 10" (3 M)                                                                        | 10' 10" (3.3 M)                                                                     | 12' 8" (3.85 M)                                                                     |
| INSIDE BEAM                    | 2' 8" (0.81 M)                                                                      | 2' 10" (0.86 M)                                                                     | 3' 3" (0.99 M)                                                                      | 3' 3" (0.99 M)                                                                      | 3' 6" (1.08 M)                                                                      |
| TUBE DIAMETER                  | 17" (0.43 M)                                                                        | 17" (0.43 M)                                                                        | 18" (0.46 M)                                                                        | 19" (0.48 M)                                                                        | 21" (0.53 M)                                                                        |
| CAPACITY PERSONS               | 6                                                                                   | 6                                                                                   | 7                                                                                   | 8                                                                                   | 10                                                                                  |
| WEIGHT                         | 227 LBS (103 KG)                                                                    | 242 LBS (110 KG)                                                                    | 282 LBS (128 KG)                                                                    | 317 LBS (144 KG)                                                                    | 480 LBS (218 KG)                                                                    |
| WEIGHT WITH BOW LOCKER         | 247 LBS (112 KG)                                                                    | 262 LBS (119 KG)                                                                    | 295 LBS (134 KG)                                                                    | 335 LBS (152 KG)                                                                    | 501 LBS (227 KG)                                                                    |
| RECOMMENDED HP                 | 20                                                                                  | 25                                                                                  | 30                                                                                  | 40                                                                                  | 50                                                                                  |
| MAXIMUM HP                     | 30                                                                                  | 30                                                                                  | 40                                                                                  | 50                                                                                  | 60                                                                                  |
| SHAFT LENGTH                   | 15" (38.1 CM)                                                                       | 15" (38.1 CM)                                                                       | 20" (50.8 CM)                                                                       | 20" (50.8 CM)                                                                       | 20" (50.8 CM)                                                                       |



PROFESSIONAL ALUMINUM CONSOLE BOATS

PROFILE A 21-XHD



OVERBUILT REINFORCED PROFESSIONAL GRADE HULL | MILITARY GRADE ORCA (CSM) FABRIC  
CUSTOMIZABLE UPON REQUEST | LARGE CAPACITY FOR CREW AND EQUIPMENT | IDEAL FOR TOUGH OPERATIONS

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Hydraulic Steering System
- Bow Locker
- Leaning Bolster
- Bow Towing Post
- Aluminum Console With Plexiglass Windshield & Rail
- Integrated Aluminum Fuel Tank
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Reinforced Aluminum Bow Eye
- Reinforced Aluminum Tow Rings
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rubrail
- 4 Aluminum Davit Lifting Points
- Non-Skid Orca (CSM) Fabric On Top Of Tube
- Heavy Duty Non-Skid Rubber Floor Panels
- 4 Layer Reinforced Seams

- Heavy Duty 1670 Decitex Orca
- Orca (CSM) Fabric
- Life Line Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Customized Aluminum Consoles And Seats
- Fiberglass Or Aluminum Jockey Consoles
- Aluminum Jockey Seats
- Bow Rider Seats
- Cover
- Lifting Harness
- Electronics Upon Requests
- T-Top
- Stern Towing Post
- Light Arch
- Engine Guard
- Color Boat Customization

| 2 MODELS • 21 AND 24 | A 21-XHD          | A 24-XHD          |
|----------------------|-------------------|-------------------|
|                      |                   |                   |
| LENGTH               | 21' (6.4 M)       | 24'8" (7.52 M)    |
| BEAM                 | 9'1" (2.77 M)     | 9'2" (2.80 M)     |
| INSIDE LENGTH        | 16'5" (5 M)       | 19'9" (6.02 M)    |
| INSIDE BEAM          | 4'6" (1.37 M)     | 4'8" (1.42 M)     |
| TUBE DIAMETER        | 22" (0.56 M)      | 24" (0.61 M)      |
| CAPACITY PERSONS     | 17                | 20                |
| WEIGHT               | 1580 LBS (717 KG) | 1758 LBS (799 KG) |
| RECOMMENDED HP       | 150               | 150               |
| MAXIMUM HP           | 200               | 250               |

## SPECIFICATIONS

| SPECIFICATIONS      |        |            |             |             |            |            |            |             | PROFILE<br>F |            |            |            |            |            |            |            | PROFILE<br>A |            |            |            |            |            |        |        | PROFILE<br>AS |        |        |      |      | PROFILE<br>A-XHD |  |
|---------------------|--------|------------|-------------|-------------|------------|------------|------------|-------------|--------------|------------|------------|------------|------------|------------|------------|------------|--------------|------------|------------|------------|------------|------------|--------|--------|---------------|--------|--------|------|------|------------------|--|
|                     |        |            |             |             |            |            |            |             | F 14         | F 15       | F 17       | F 19       | F 21       | F 24       | F 28       | A 11       | A 12         | A 13       | A 14       | A 15       | A 16       | A 18       | A 11-S | A 12-S | F 13-S        | A 14-S | A 16-S | A 21 | A 24 |                  |  |
| LENGTH              |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| OVERALL             | ft/in  | 14'        | 15'         | 17'         | 19'        | 21' 4"     | 24'        | 27'         | 11'6"        | 12'        | 13'        | 14'        | 15'        | 16'        | 18'        | 11'6"      | 12'          | 13'        | 14'        | 16'        | 21'        | 24' 8"     |        |        |               |        |        |      |      |                  |  |
|                     | m      | 4.27       | 4.57        | 5.18        | 5.79       | 6.50       | 7.31       | 8.23        | 3.5          | 3.66       | 3.96       | 4.27       | 4.57       | 4.88       | 5.49       | 3.5        | 3.66         | 3.96       | 4.27       | 4.88       | 6.4        | 7.52       |        |        |               |        |        |      |      |                  |  |
| INSIDE              | ft/in  | 10'10"     | 11'6"       | 13'1"       | 15'2"      | 17' 3"     | 19'3"      | 22' 11"     | 8'6"         | 8'10"      | 9'10"      | 10'10"     | 11'8"      | 13' 2"     | 14'8"      | 8'6"       | 8'10"        | 9'10"      | 10'10"     | 12' 8"     | 16' 5"     | 19' 9"     |        |        |               |        |        |      |      |                  |  |
|                     | m      | 3.3        | 3.5         | 4           | 4.62       | 5.25       | 5.87       | 6.99        | 2.6          | 2.7        | 3          | 3.3        | 3.55       | 3.85       | 4.47       | 2.6        | 2.7          | 3          | 3.3        | 3.85       | 5          | 6.02       |        |        |               |        |        |      |      |                  |  |
| BEAM                |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| OVERALL             | ft/in  | 6'4"       | 6'6"        | 8'1"        | 8'4"       | 8'10"      | 9'3"       | 10'11"      | 5'7"         | 6'1"       | 6'7"       | 6'7"       | 6'9"       | 7"         | 7'11"      | 5'7"       | 5'11"        | 6'5"       | 6'5"       | 7"         | 9'1"       | 9'2"       |        |        |               |        |        |      |      |                  |  |
|                     | m      | 1.94       | 1.99        | 2.46        | 2.53       | 2.70       | 2.82       | 3.07        | 1.7          | 1.85       | 2          | 2          | 2.06       | 2.14       | 2.40       | 1.7        | 1.8          | 1.96       | 1.96       | 2.14       | 2.77       | 2.80       |        |        |               |        |        |      |      |                  |  |
| INSIDE              | ft/in  | 3' 1"      | 3'2"        | 4'4"        | 4'1"       | 4'9"       | 5'4"       | 6' 4"       | 2'8"         | 2'11"      | 3'3"       | 3'3"       | 3'4"       | 3'6"       | 4'3"       | 2'8"       | 2'10"        | 3'3"       | 3'3"       | 3'6"       | 4'6"       | 4' 8"      |        |        |               |        |        |      |      |                  |  |
|                     | m      | 0.94       | 0.97        | 1.33        | 1.25       | 1.44       | 1.64       | 1.93        | 0.81         | 0.89       | 0.99       | 0.99       | 1.03       | 1.08       | 1.30       | 0.81       | 0.86         | 0.99       | 0.99       | 1.08       | 1.37       | 1.42       |        |        |               |        |        |      |      |                  |  |
| AREA                |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| INTERNAL AREA       | sq.ft. | 33.39      | 36.54       | 57.26       | 62.16      | 81.38      | 103.62     | 145.21      | 22.67        | 25.87      | 31.97      | 35.17      | 39.36      | 44.76      | 62.55      | 22.67      | 25           | 31.97      | 35.17      | 44.76      | 73.73      | 92.01      |        |        |               |        |        |      |      |                  |  |
|                     | m2     | 3.10       | 3.40        | 5.32        | 5.78       | 7.56       | 9.63       | 13.49       | 2.11         | 2.40       | 2.97       | 3.27       | 3.66       | 4.16       | 5.81       | 2.11       | 2.32         | 2.97       | 3.27       | 4.16       | 6.85       | 8.55       |        |        |               |        |        |      |      |                  |  |
| MAX TUBE DIAMETER   |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
|                     | ft/in  | 19"        | 19"         | 20"         | 22"        | 22"        | 24"        | 24"         | 17"          | 17"        | 18"        | 19"        | 19"        | 21"        | 21"        | 17"        | 17"          | 18"        | 19"        | 21"        | 22"        | 24"        |        |        |               |        |        |      |      |                  |  |
|                     | m      | 0.48       | 0.48        | 0.50        | 0.56       | 0.56       | 0.61       | 0.61        | 0.43         | 0.43       | 0.46       | 0.48       | 0.48       | 0.53       | 0.53       | 0.43       | 0.43         | 0.46       | 0.48       | 0.53       | 0.56       | 0.61       |        |        |               |        |        |      |      |                  |  |
| NUMBER OF CHAMBERS  |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
|                     |        | 4+1        | 5           | 5           | 5          | 5          | 6          | 6           | 3            | 3          | 3          | 4          | 5          | 5          | 5          | 3          | 3            | 3          | 4          | 5          | 6          | 6          |        |        |               |        |        |      |      |                  |  |
| CAPACITY            |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| PERSONS             |        | 8          | 11          | 15          | 15         | 20         | 20         | 25          | 6            | 6          | 7          | 8          | 9          | 10         | 15         | 6          | 6            | 7          | 8          | 10         | 17         | 20         |        |        |               |        |        |      |      |                  |  |
| PAYLOAD             | lbs    | 2,347      | 2,557       | 2,965       | 3,999      | 4,100      | 4,526      | 5,035       | 1,644        | 2,032      | 2,092      | 2,392      | 2,608      | 2,600      | 3,053      | 1,644      | 2,032        | 2,092      | 2,391      | 2,709      | 3,915      | 4,526      |        |        |               |        |        |      |      |                  |  |
|                     | kg     | 1,065      | 1,160       | 1,345       | 1,814      | 1,860      | 2,053      | 2,284       | 746          | 922        | 949        | 1,085      | 1,183      | 1,179      | 1,385      | 746        | 922          | 949        | 1,085      | 1,229      | 1,776      | 2,053      |        |        |               |        |        |      |      |                  |  |
| WEIGHT              |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
|                     | lbs    | 403 *      | 484 *       | 772 *       | 1157       | 1642       | 1980       | 2853        | 214          | 231        | 256        | 287        | 383        | 438        | 859        | 227        | 242          | 282        | 317        | 480        | 1580       | 1758       |        |        |               |        |        |      |      |                  |  |
|                     | kg     | 183 *      | 220 *       | 350 *       | 526        | 745        | 900        | 1297        | 97           | 105        | 116        | 130        | 174        | 199        | 390        | 103        | 110          | 128        | 144        | 218        | 717        | 799        |        |        |               |        |        |      |      |                  |  |
| WITH BOW LOCKER     | lbs    |            |             |             |            |            |            |             | 229          | 250        | 311        | 312        | 421        | 479        |            | 247        | 262          | 295        | 335        | 501        |            |            |        |        |               |        |        |      |      |                  |  |
|                     | kg     |            |             |             |            |            |            |             | 104          | 113        | 141        | 142        | 191        | 217        |            | 112        | 119          | 134        | 152        | 227        |            |            |        |        |               |        |        |      |      |                  |  |
| ENGINE              |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| RECOMMENDED         | hp     | 40         | 60          | 75          | 115        | 150        | 150        | 250         | 20           | 25         | 30         | 40         | 50         | 50         | 90         | 20         | 25           | 30         | 40         | 50         | 150        | 150        |        |        |               |        |        |      |      |                  |  |
|                     | kW     | 29.8       | 44.8        | 56          | 85.8       | 111.9      | 111.9      | 186.5       | 14.9         | 18.7       | 22.4       | 29.8       | 37         | 37         | 67         | 14.9       | 18.7         | 22.4       | 29.8       | 37         | 111.9      | 111.9      |        |        |               |        |        |      |      |                  |  |
| MAX                 | hp     | 50         | 75          | 90          | 150        | 225        | 250        | 500         | 30           | 30         | 40         | 50         | 60         | 70         | 115        | 30         | 30           | 40         | 50         | 60         | 200        | 250        |        |        |               |        |        |      |      |                  |  |
|                     | kW     | 37.3       | 56          | 67          | 111.9      | 186.5      | 186.5      | 373.0       | 22.4         | 22.4       | 29.8       | 37         | 44.8       | 52.2       | 85.8       | 22.4       | 22.4         | 29.8       | 37         | 44.8       | 149        | 186.5      |        |        |               |        |        |      |      |                  |  |
| SHAFT LENGTH        | in     | 20"        | 20"         | 20"         | 25"        | 25"        | 25"        | 30"         | 20"          | 20"        | 20"        | 20"        | 20"        | 20"        | 25"        | 15"        | 15"          | 20"        | 20"        | 20"        | 25"        | 25"        |        |        |               |        |        |      |      |                  |  |
|                     | cm     | 50.8       | 50.8        | 50.8        | 63.5       | 63.5       | 63.5       | 76.2        | 50.8         | 50.8       | 50.8       | 50.8       | 50.8       | 50.8       | 63.5       | 38.1       | 38.1         | 50.8       | 50.8       | 50.8       | 63.5       | 63.5       |        |        |               |        |        |      |      |                  |  |
| MAX WEIGHT          | lbs    | 253        | 330         | 365         | 515        | 683        | 814        | 1240        | 132          | 183        | 182        | 242        | 242        | 253        | 484        | 132        | 182          | 182        | 242        | 253        | 771        | 814        |        |        |               |        |        |      |      |                  |  |
|                     | kg     | 115        | 150         | 166         | 234        | 310        | 370        | 564         | 60           | 83         | 83         | 110        | 110        | 115        | 220        | 60         | 83           | 83         | 110        | 115        | 350        | 370        |        |        |               |        |        |      |      |                  |  |
| BUILT-IN TANKS      |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| GAS                 | gal    | N/A        | 27***       | 34***       | 49         | 63         | 65         | 189         |              |            |            |            | 16***      | 16***      | 32         |            |              |            |            |            | 55         | 59         |        |        |               |        |        |      |      |                  |  |
|                     | lt     | N/A        | 102***      | 128***      | 185        | 240        | 246        | 715         |              |            |            |            | 60***      | 60***      | 120        |            |              |            |            |            | 208        | 223        |        |        |               |        |        |      |      |                  |  |
| WATER               | gal    |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
|                     | lt     |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| STOWED DIMENSIONS   |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
| LENGTHXWIDTHXHEIGHT | inch   | 156x49x28  | 169x59x43   | 192x54x47   | 213x75x32  | 238x81x36  | 276x87x35  | 323x113x47  | 132x44x19    | 138x46x26  | 144x47x32  | 159x47x32  | 167x47x32  | 182x55x32  | 214x71x38  | 132x44x19  | 138x46x26    | 144x47x32  | 159x47x32  | 182x55x32  | 234x83x38  | 270x83x38  |        |        |               |        |        |      |      |                  |  |
|                     | cm     | 395x125x70 | 430x150x110 | 490x137x130 | 540x190x82 | 605x206x91 | 700x220x90 | 820x288x220 | 334x113x47   | 350x116x65 | 365x120x82 | 405x120x82 | 425x120x82 | 463x140x82 | 544x180x97 | 334x113x47 | 350x116x65   | 365x120x82 | 405x120x82 | 463x140x82 | 594x211x97 | 686x211x97 |        |        |               |        |        |      |      |                  |  |
| RBC DESIGN CATEGORY |        |            |             |             |            |            |            |             |              |            |            |            |            |            |            |            |              |            |            |            |            |            |        |        |               |        |        |      |      |                  |  |
|                     |        | C          | C           | C           | C          | C          | B          | B           | C            | C          | C          | C          | C          | C          | C          | C          | C            | C          | C          | C          | C          | C          |        |        |               |        |        |      |      |                  |  |

\* WEIGHT SPEC APPLIES FOR THE OPEN VERSION

---

\*\*\* OPTIONAL FUEL TANK

---

FEATURES FOR THE F 14, F15 AND F 17 STATED ARE FOR THE OPEN VERSION

---

EPA COMPLIANT FUEL TANKS, 7% REDUCTION APPROXIMATELY

---



| FEATURES                                             | PROFILE<br>F |      |      |      |      |      |      | PROFILE<br>A |      |      |      |      |      |      | PROFILE<br>AS |        |        |        |        | PROFILE<br>A-XHD |          |   |
|------------------------------------------------------|--------------|------|------|------|------|------|------|--------------|------|------|------|------|------|------|---------------|--------|--------|--------|--------|------------------|----------|---|
|                                                      | F 14         | F 15 | F 17 | F 19 | F 21 | F 24 | F 28 | A 11         | A 12 | A 13 | A 14 | A 15 | A 16 | A 18 | A 11-S        | A 12-S | A 13-S | A 14-S | A 16-S | A 21-XHD         | A 24-XHD |   |
| STANDARD FEATURES ●                                  |              |      |      |      |      |      |      |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| OPTIONAL FEATURES ○                                  |              |      |      |      |      |      |      |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| (CSM) COATED FABRIC 1670 D-TEX FABRIC                | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| (CSM) COATED FABRIC NON-SKID ON TUBES                | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| LED ALL AROUND ANCHOR LIGHT                          | ○            | ○    | ○    | ●    | ●    | ●    | ●    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ●                | ●        |   |
| BENCH SEAT WITH STORAGE                              | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| BOW AND LATERAL REINFORCED COATED FABRIC HANDLES     | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| BOW EYE - ALUMINUM                                   |              |      |      |      |      |      |      | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| BOW EYE - STAINLESS STEEL                            | ●            | ●    | ●    | ●    | ●    | ●    | ●    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| BOW SEAT WITH STORAGE                                | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| BOW SEAT WITH STORAGE & PORTABLE 6 GALLON FUEL TANK  |              |      |      |      |      |      |      | ○            | ○    | ○    | ○    | ○    | ○    | ○    |               |        |        |        |        |                  |          |   |
| CARBON FIBER LOOK SWITCH WITH BRAKER BOARD           |              |      |      | ●    | ●    | ●    | ●    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| CONSOLE ALUMINUM                                     |              |      |      |      |      |      |      | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| CONSOLE WITH FORWARD SEAT                            | ○            | ○    | ○    | ○    | ○    | ○    | ○    |              |      | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| DAVIT LIFTING RINGS - ALUMINUM                       |              |      |      |      |      |      |      | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| DAVIT LIFTING RINGS - STAINLESS STEEL                | ●            | ●    | ●    | ●    | ○    | ○    | ○    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| DOUBLE SOLID RUB RAIL                                | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| ENGINE GUARD                                         | ○            | ○    | ○    | ○    | ○    | ○    | ○    |              |      |      |      |      | ○    | ○    |               |        |        |        | ○      | ○                | ○        |   |
| FIBERGLASS BOW STEP WITH SS RETRACTING CLEAT         | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| FIBERGLASS CONSOLE WITH WINDSHIELD AND RAIL          | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| FUEL SENDING UNIT                                    | ○            |      | ○    | ○    | ○    | ○    | ○    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| INTEGRATED ALUMINUM FUEL TANK                        |              | ○    | ○    | ○    | ○    | ○    | ○    |              |      |      |      | ○    | ○    | ●    |               |        |        |        |        | ●                | ●        |   |
| FUEL/WATER SEPARATOR & CANISTER                      | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| HAND PUMP/REPAIR KIT                                 | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| JOCKEY CONSOLE (1 PERSON)                            | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| JOCKEY CONSOLE ( 2 PERSON)                           | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| LEANING BOLSTER                                      |              |      |      |      |      |      |      |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| LIFELINE AROUND TUBE                                 | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| LIGHT ARCH                                           |              | ○    | ○    | ○    | ○    | ○    | ○    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| LED NAVIGATION LIGHTS                                | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| NON SKID DECK - DIAMOND SHAPE                        | ●            | ●    | ●    | ●    | ●    | ●    | ●    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| SEADEK® EVA FOAM NON-SKID FLOOR                      |              |      |      |      | ○    | ○    | ○    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| SLIP RESISTANT SURFACE                               |              |      |      |      |      |      |      |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| PADDLES                                              | ●            | ●    | ●    |      |      |      |      | ●            | ●    | ●    | ●    | ●    | ●    |      | ●             | ●      | ●      | ●      | ●      |                  |          |   |
| REINFORCED TRANSOM KNEES                             |              |      |      |      |      |      |      | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        | ● |
| RUBBER KEEL PROTECTOR                                | ●            | ●    |      |      |      |      |      | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      |                  |          |   |
| WELDED ALUMINUM KEEL PROTECTOR                       |              |      |      |      |      |      |      |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| PRESSURE RELIEF VALVES                               | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| SIDE STEP/STAINLESS STEEL FOLD DOWN CLEAT            | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |
| TOWING POST - BOW                                    |              |      |      | ○    | ○    | ○    | ○    |              |      |      |      |      |      | ○    |               |        |        |        |        | ○                | ○        |   |
| TOWING POST - STERN                                  |              |      |      | ○    | ○    | ○    | ○    | ○            |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| TOWING EYES - STERN (ALUMINUM)                       |              |      |      |      |      |      |      | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| TOWING EYES - STERN (STAINLESS STEEL)                | ●            | ●    | ●    | ●    | ●    | ●    | ●    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| TRANSOM ELEPHANT NOSE SCUPPERS (2 7/8 IN INTERNAL Ø) |              | ●    | ●    |      |      |      |      | ●            | ●    | ●    | ●    | ●    | ●    | ●    | ●             | ●      | ●      | ●      | ●      | ●                | ●        |   |
| T-TOP                                                |              |      |      | ○    | ○    | ○    | ○    |              |      |      |      |      |      |      |               |        |        |        |        |                  |          |   |
| FULLY UPHOLSTERED SEATING SPRADLING®                 | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○            | ○    | ○    | ○    | ○    | ○    | ○    | ○             | ○      | ○      | ○      | ○      | ○                | ○        |   |

FOR ADDITIONAL INFORMATION AND LISTING OF WORLDWIDE DEALERS VISIT US AT [ABINFLATABLES.COM](http://ABINFLATABLES.COM)