

STANDARD FEATURES

- Mechanical Steering System and Sporty Wheel
- Standard Rigging From Factory
- Integrated fiberglass console with space for a 7"GPS
- Bow locker with capacity for a 6-gallon portable fuel tank
- Bow locker seat with cushion
- Removable lateral console seat
- Splashwell and rear seat equipped with sturdy SS hinges
- Under seat storage compartment
- Stainless Steel Bow Eye
- USB-C Port &12V DC outlet
- LED Navigation Lights
- All Around Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fully Upholstered Seating - Spradling®
- 4 Stainless Steel Davit Lifting Points
- Solid Single Rub Rail
- Stainless Steel Tow Rings
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 3 Layers Reinforced Seams
- Orca (CSM) Coated Fabric
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Cupholder



OPTIONAL FEATURES

- Tube Chaps
- Cover
- Chock Set
- Bimini Top
- Lifting Harness
- Stereo System
- Compass
- GPS
- VHF Radio
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Color Boat Customization
- Hydraulic Steering System
- Synthetic Teak Floor
- Seadek ® Foam Teak (Grey or Mocca)

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	10' 6"	3.19 M
OVERALL BEAM	5' 7"	1.72 M
INSIDE LENGTH	7' 7"	2.31 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	4	4
WEIGHT	304 LBS	138 KG
MAXIMUM HP	30 HP	22.4 KW
RDC DESIGN CATEGORY	C	C
SHAFT LENGTH	15" - 20"	38,1 - 50.8 CM

STANDARD FEATURES

- Mechanical Steering System and Sport Steering Wheel
- Standard Rigging From Factory
- Stainless Steel Bow Eye
- Bow Locker Seat & Cushion
- Integrated Fiberglass Console
- Foldable Console
- Plexiglass Windshield
- SS LED Side Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fully Upholstered Seating - Spradling ®
- Under Seat Storage Compartments
- 4 Stainless Steel Davit Lifting Points
- Solid Single Rub Rail
- Stainless Steel Tow Rings
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Orca (CSM) Coated Fabric
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Cupholder
- Removable Lateral Seat
- Bow Locker Seat with Vent & Storage to Fit a 6 Gal Portable Fuel Tank



STANDARD REMOVABLE LATERAL SEAT



OPTIONAL FEATURES

- Tube Chaps
- Cover
- Chock Set
- Bimini Top
- Lifting Harness
- Stereo System
- Compass
- GPS
- VHF Radio
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Color Boat Customization
- Hydraulic Steering System
- Synthetic Teak Floor
- Seadek ® Foam Teak (Grey or Mocca)

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	11' 4"	3.45 M
OVERALL BEAM	5' 9"	1.77 M
INSIDE LENGTH	8' 1"	2.47 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	4	4
WEIGHT	317 LBS	144 KG
MAXIMUM HP	40 HP	29.8 KW
RDC DESIGN CATEGORY	C	C
SHAFT LENGTH	20"	50.8 CM

STANDARD FEATURES

- Mechanical Steering System and Sport Steering Wheel
- Standard Rigging From Factory
- Stainless Steel Bow Eye
- Bow Locker Seat & Cushion
- Integrated Fiberglass Console
- Plexiglass Windshield
- SS LED Side Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fully Upholstered Seating - Spradling ®
- Under Seat Storage Compartments
- 4 Stainless Steel Davit Lifting Points
- Solid Single Rub Rail
- Stainless Steel Tow Rings
- Reinforced Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Orca (CSM) Coated Fabric
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Cupholder



OPTIONAL FEATURES

- Tube Chaps
- Cover
- Chock Set
- Bimini Top
- Lifting Harness
- Stereo System
- Compass
- GPS
- VHF Radio
- Bow Step with Stainless Steel Fold Down Cleat
- Lateral Stainless Steel Fold Down Cleat
- Color Boat Customization
- Hydraulic Steering System
- Synthetic Teak Floor
- Seadek ® Foam Teak (Grey or Mocca)

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	12'	3.66 M
OVERALL BEAM	6'	1.82 M
INSIDE LENGTH	8' 9"	2.67 M
INSIDE BEAM	2' 9"	0.84 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	5	5
WEIGHT	337 LBS	153 KG
MAXIMUM HP	40 HP	29.8 KW
RDC DESIGN CATEGORY	C	C
SHAFT LENGTH	20"	50.8 CM